

USED ON JLG



HARDWARE

AXLES/PINS					
	Diameter mm	Total length mm	Hardened	Used on	REF
	4	23	No	H340AJ, 340AJ, 400S/460SJ, 450AJ, E/M450A/AJ, M/E600/J/JP, 740AJ, 800A/AJ	126TA5219
	12	42	No	1932R, 20/2632ES, 1930ES, 1930/2030/2630/2646/3246ES	126TA5714
	12,5	39	No	1532/2658E, 1532/3246E2, 1532/2658E3, 1532/1932/2033/2046/2646, 2658E	126TA5715
	12,5	55	No	600A/AJ, 1932R, 1500AJP, 740AJ, 600SC/SJC	126TA5044
	25,4	195,4	No	600A/AJ, 600S/SJ/660SJ, 740AJ, 400S/460SJ, 800A/800AJ	126TA5040
	25,4	240	No	600A/AJ, 600S/SJ/660SJ, 800A/AJ, 450A/AJ	126TA5039
	25,4	280	No	H340AJ, 340AJ, 450AJ, 520AJ, E/M600/J/JP	139TA5158
	25,4	385	No	600A/AJ, 600S/SJ/660SJ, 800A/AJ	139TA5156
	31,7	243	No	3369/4069LE/M3369/4069	126TA5041

USED ON JLG



AXLES/PINS					
	Diameter mm	Total length mm	Hardened	Used on	REF
	31,7	260	Yes	H340AJ, T350/T500J, M/E600/J/JP, 450AJ, 340AJ	139TA5157
	31,7	292,1	No	510AJ, M/E600/J/JP, E/M450A/AJ	139TA5159
	31,7	71	No	400S/460SJ, 400S/SJ, 340AJ, 3394/4394RT, 450A/AJ, 510AJ	165TA4359
	31,7	65	No	450A/AJ, 400S/400SJ, 400S/460SJ, 510AJ, 3394/4394RT, 450A/AJ SERIES II	126TA5712
	31,8	240	No	R10, 600A/AJ, 6/10/1932/3248RS, 740AJ, 600SC/SJC, 400S/460SJ, 800A/AJ	139TA5160
	32	255,5	No	400S/460SJ, 450A/AJ, E/M600J(IP), 3394/4394RT	126TA5035
	38	78	No	600A/AJ	126TA5713
	38	250	No	520AJ, M/E600/J/JP, 450A/AJ, 800S/860SJ	126TA5037
	50,8	95	No	600S/SJ/660SJ, 740AJ, 800A/AJ	126TA5036

HARDWARE

USED ON JLG



HARDWARE

CENTER BOLTS



- Diameter: 19 mm
- Length: 72,5 mm
- External thread: 5/8" UNC
- Imperial pitch: 11 Pi
- Length of thread: 17 mm

Used on 1930ES

REF [165TA4361](#)



- Diameter: 19 mm
- Length: 79,2 mm
- External thread: 5/8" UNC
- Imperial pitch: 11 Pi
- Length of thread: 18 mm

Used on 1200SJP, 1250AJP, 1500SJ, 1100S, 1100SB

REF [126TA5828](#)



- Diameter: 31,7 mm
- Length: 79,2 mm
- External thread: 7/8" UNC
- Imperial pitch: 9 Pi
- Length of thread: 24 mm

Used on E300A

REF [165TA4362](#)

LOCKING PINS

	Diameter pin mm	Total length mm	Used on	REF
	6	75	R10, 260MRT, 1932R, 6/10/1932/3248RS	126TA5724
	25,5	52	20/25/30/36/41(AM), 15/20MSP/MVL, 12SP/15SP, 10MSP	126TA5727
	7,8	77,5	260MRT, T350/T500J, 600A/AJ, 1500JP, 530LRT, E/M600J/JP	126TA5723

USED ON JLG



LOCKING PINS				
	Diameter pin mm	Total length mm	Used on	REF
	6,3	58	20/25/30/36/41(AM), G15/44A, 10MSP, G6/42A-G9/10-43A, 600A/AJ, 1500AJP, 33/4394	127TA2680
	9,2	78,2		127TA2702
	6	57,7	R6, R10, 1932R, 6/10/1932/3248RS, 20/2632ES	165TA4360

HARDWARE

USED ON JLG



OTHER PARTS

SAFE-T-LOCK

SAFE-T-LOCK™**Safe-T-Lock STL 1000**

Suitable for all types of voltages, the Safe-T-Lock is the most easy-to-use and fast to program access control device in our range. It can hold up to 99 user codes.

Features:

- Voltage: 12-120 VDC
- Waterproof IP65
- Up to 99 different users/drivers (settings can only be changed by a supervisor)
- 1 programmable supervisor code
- Last user identification
- Automatic shut-off after 3 minutes (fixed time) of vehicle inactivity
- Maintenance alert after 250 hours

Used on 1230ES, 1532E3 from serial n° 0200000000 to 0200999999, E400A, 1930ES, 3246E2, T350, 450A, E600, 1532E, 1200SJP, 3369LE, E45A, 1250AJP, 400S, 600SC, 800S, 600S, 600A from serial n° 0300000000 to 0300099999, 3394RT, 510AJ, 1500SJ, 340AJ, 1100S, G9-43A, 1532E2, 266, 680S, 800A, G5-19A, 1100SB, 400SC

REF [125TA5079](#)

HANDSET FOR JLG

**To program JLG machines**

The analyser kit is essential for programming and troubleshooting JLG mobile elevating work platforms. This is a must have tool for any service technician.

Features/benefits:

- Compact-size tool that you can carry with you to your job site
- Quick diagnostic for fault codes
- Adjust machine parameters on-site
- Enable and disable machine features
- Configure new options
- High-contrast LCD screen

Used on R6, R10, G6/42A-G9/10-43A, 600A/AJ, T350/500J, 520AJ

REF [126TA5316](#)

USED ON JLG



OTHER PARTS

CABLE FOR HANDSET



Replacement cable

Used on 1230ES, 1532E3 from serial n° 0200000000 to 0200999999, 3246E2, 1532E, 800A, 1200SJP, 1250AJP, 600SC, 800S, 600S, 600A from serial n° 0300000000 to 0300099999, 450A, 1500SJ, 340AJ, 1100S, G9-43A, 1532E2, 1930ES, 680S, 1100SB

REF [164TA8212](#)

MOS90 HANDSET



For the programming of JLG machines that are equipped with Sevcon MOS90 controllers.

- Controller type: MOS90
- Type: electric machines
- Serial communication

Used on 100SX, 400S, 30E, E300A, 450A, 600A from serial n° 0300000000 to 0300099999, 600SC, 800A, 1200SJP, 3369ELECTRIC, E600, E45A, E400A, 1250AJP, 450AJ, 800S, 600S, 510AJ, 1500SJ, 340AJ, 1100S, 1850SJ, 680S, 1100SB, TF6-42, 400SC

REF [106TA6377](#)

MOBILE ANALYSER



The JLG mobile analyser is a Wi-Fi enabled evolution of the handheld analyser kit, allowing technicians to do the same analysis they are currently doing with the handheld kit. However, this new tool for Apple and Google operating system devices, allows for an extended operating range of up to 150 ft.

Features/benefits:

- Compatible with Apple iOS 5.0 and up, plus Android API 8 and up
- Works with JLG products that are equipped with Advanced Design Electronics (ADE)
- Allows for extended operator range of up to 150 ft
- Available in multiple languages, with more languages to be added
- Interchangeable between machines (note: it can only be connected to one mobile device at a time)
- Analyser training is included as part of all JLG factory training
- Displays full description read-outs instead of abbreviated scrolling text

REF [152TA1931](#)

USED ON JLG



NOTES

A large area of horizontal dotted lines for taking notes.