

USED ON JLG



WHEELS, TYRES & RUBBER TRACKS

LOAD WHEEL



- Diameter wheel: 200 mm
- Width wheel: 63 mm
- Diameter shaft: 20 mm

Used on E300A, E45A, E400A

REF [151TA2916](#)

SOLID TYRE KIT



- Tyre size: 25 x 7 x 12

Used on 1200SJP, 1250AJP, 1500SJ, 1100S, 1850SJ, 1100SB, TOUCAN DUO, 13MSPT

REF [165TA4319](#)

ANTI-PUNCTURE TYRES



- Foam filled wheel assembly
- Tyre size: 445/65 x 22,5

Used on 600A from serial n° 0300000000 to 0300099999, 100 SX, 110 SX, 110 SXJ, 120SXJ

REF [165TA4313](#) - LH
REF [165TA4314](#) - RH



- Foam filled wheel assembly
- Tyre size: 14 x 17,5

Used on 3369LE, E45A, E400A, 600A from serial n° 0300000000 to 0300099999, 601S

REF [165TA4320](#) - LH
REF [165TA4321](#) - RH



- Foam filled wheel assembly
- Tyre size: 625 x 298

Used on 600AJ

REF [165TA4315](#) - LH
REF [165TA4316](#) - RH



- Foam filled wheel assembly
- Tyre size: 15 x 19,5

Used on 800AJ

REF [165TA4322](#) - LH
REF [165TA4323](#) - RH



- Foam filled wheel assembly
- Tyre size: 16-625

Used on 800AJ, 800SJ, 860SJ

REF [165TA4317](#) - LH
REF [165TA4318](#) - RH



- Foam filled wheel assembly
- Tyre size: 18-625

Used on 800AJ, 800SJ, 860SJ

REF [165TA4324](#) - LH
REF [165TA4325](#) - RH

USED ON JLG



WHEELS, TYRES & RUBBER TRACKS

ANTI-PUNCTURE TYRES



- Foam filled wheel assembly
- Tyre size: 15 x 28

Used on 1250AJP, 1350SJP, 1500SJ

REF [165TA4326](#) - LH
REF [165TA4327](#) - RH



- Foam filled wheel assembly
- Tyre size: 33/1550 x 16,5

Used on 3394RT, 4394RT, 450AJ, 510AJ

REF [165TA4332](#) - LH
REF [165TA4333](#) - RH



- Foam filled wheel assembly
- Tyre size: 15 x 19,5

Used on 600SJ

REF [165TA4328](#) - LH
REF [165TA4329](#) - RH



- Foam filled wheel assembly
- Tyre size: 15 x 19,5

Used on 600SJ

REF [165TA4334](#) - LH
REF [165TA4335](#) - RH



- Foam filled wheel assembly
- Tyre size: 12 x 16,5

Used on 400RTD, 500RTS, 25RTS, 33RTS, 40RTS

REF [165TA4330](#) - LH
REF [165TA4331](#) - RH



- Foam filled wheel assembly
- Tyre size: IN240/55 x 17,5

Used on E400A, 4069LE

REF [165TA4336](#)

USED ON JLG



TRACTION WHEELS						
	Diameter wheel mm	Number of bolt holes	Width wheel mm	Diameter shaft mm	Used on	REF
	300	4	85	72	TOUCAN JUNIOR 6, TOUCAN DUO, TOUCAN JUNIOR 8, V1331E, VM1931E, 13MSPT	165TA4337
	300	0	80	27,5	TOUCAN JUNIOR 6, TOUCAN JUNIOR 8, TOUCAN JUNIOR 6/8B, VM1931E, V1331E	145TA9131
	302	5	100	72		164TA1345
	302	5	99	72		164TA1344
	310	5	100	72	600A from serial n° 0300000000 to 0300099999	147TA2854
	310	5	99	72		151TA2325
	316	5	108	86	1532/3246E2, 1532/1932/2032/2632/2646/3246E2	165TA4338
	323	5	100	186	TOUCAN1100A	126TA5936

WHEELS, TYRES & RUBBER TRACKS

USED ON JLG



WHEELS, TYRES & RUBBER TRACKS

TRACTION WHEELS						
	Diameter wheel mm	Number of bolt holes	Width wheel mm	Diameter shaft mm	Used on	REF
	323	5	100	186,6	3246E2, 1532E, 1532E3 from serial n° 0200000000 to 0200999999, 1532E2	126TA5139
	323	5	100	187	R6, 6/10/1932/3248RS	165TA4339
	354	5	114	86	3369LE, E400A	126TA5939
	354	5	114	86	600A from serial n° 0300000000 to 0300099999, 67SL	141TA4893
	404	5	125	86	R10, 6/10/1932/3248RS	165TA4340
	406	4	126	85	TOUCAN1010, TOUCAN910	165TA3947
	406	4	127	28	TOUCAN1100A, TOUCAN1010, TOUCAN1100, TOUCAN910, V2642E	145TA9140
	406	5	125	186	1930ES	151TA2438

USED ON JLG



TRACTION WHEELS						
	Diameter wheel mm	Number of bolt holes	Width wheel mm	Diameter shaft mm	Used on	REF
	406	5	127	85	1532E, 1532E3 from serial n° 0200000000 to 0200999999	126TA5938
	406	5	127	95	SSV10	165TA3950
	406,5	5	127	86	3246E2, 1532E, 1532E3 from serial n° 0200000000 to 0200999999, CM1432, 1532E2	129TA9006
	559	9	152	203	E/M400/450A/AJ/AJP NARROW	165TA4341
	630	6	203	160	SL153-12E, SL180-12E	165TA4342
	635	9	171,5	203		165TA4343
	635	9	171	202	E300A, E300AJ, E300AJP	147TA2982

WHEELS, TYRES & RUBBER TRACKS



USED ON JLG



WHEELS, TYRES & RUBBER TRACKS

PNEUMATIC TYRES					
	Dimensions of the tyre	Ply rating	Quality	Used on	REF
	10 x 16,5	10PR	TL = tubeless	330CRT/400CRT	165TA4344
	12 x 16,5	12PR	TL = tubeless	450A, 450AJ, 3394RT, 510AJ	152TA1872
	15 x 625	16PR	TL = tubeless	3369LE, E45A, E400A	141TA3243
	18 x 625	16PR	TL = tubeless	1532E, 1532E3 from serial n° 0200000000 to 0200999999	126TA5934
	240 x 55 x 17,5	12PR	TL = tubeless	100SX	165TA4345
	240 x 55 x 17,5	12PR	TL = tubeless	E400A	165TA4346

USED ON JLG



PNEUMATIC TYRES					
	Dimensions of the tyre	Ply rating	Quality	Used on	REF
	33 x 15,5 x 16,5	12PR	TL = tubeless	100SX	165TA4347
	355 x 55 x 62	14PR	TL = tubeless	CM2033, CM1432	152TA1860
	385 x 65 x 22,5	16PR	TL = tubeless	800A	161TA1355
	445 x 55 x 19,5	16PR	TL = tubeless	800A/800AJ	152TA1861
	445 x 50 x 710	18PR	TL = tubeless	800A, 800S, 680S	152TA1862

WHEELS, TYRES & RUBBER TRACKS



USED ON JLG



WHEELS, TYRES & RUBBER TRACKS

RIMS



- Rim diameter: 19 1/2"
- Rim width: 11 3/4"
- Number of fixation holes: 10
- Type: 1 side spherical

Used on 1930ES, 1230ES

REF [165TA4348](#)

- Rim diameter: 24 1/2"
- Rim width: 11 3/4"
- Number of fixation holes: 9
- Type: 1 side spherical

Used on 800A, 800S, 680S

REF [165TA4350](#)

- Rim diameter: 24 1/2"
- Rim width: 15"
- Number of fixation holes: 10
- Type: 1 side spherical

Used on 600S, 800A, 601S

REF [126TA5143](#)

WHEEL BOLTS



- Length: 44,5 mm
- Thread type: M12
- Metric pitch: 1,5 mm
- RH/LH: RH

Used on 260MRT, 330CRT, 3369LE, E600

REF [165TA4349](#)

- Neck diameter: 13,8 mm
- Length: 45,5 mm
- Thread type: 1/2" UNF
- Imperial pitch: 20 Pi
- RH/LH: RH

Used on 1930ES, 1230ES, TOUCAN 8E, TOUCAN 10E

REF [126TA5105](#)

- Neck diameter: 16,2 mm
- Length: 61 mm
- Thread type: 5/8" UNF
- Imperial pitch: 18 Pi
- RH/LH: RH

Used on 450A, 3246E2, 26MRT, 400S, 1532E, 1532E3 from serial n° 0200000000 to 0200999999, 450AJ, 1532E2

REF [128TA3409](#)

- Neck diameter: 18,3 mm
- Length: 46,3 mm
- Thread type: M14
- Metric pitch: 1,5 mm
- RH/LH: RH

Used on 260MRT, 330CRT, 3369LE, E600

REF [165TA4351](#)

USED ON JLG



WHEEL NUTS



- Type: cone head
- Thread: 1/2" UNF
- RH/LH: RH
- Pitch: 20"
- Wrench opening: 20,64 mm

Used on CM2033, CM1432, 3246E2, 1532E, 1532E3 from serial n° 0200000000 to 0200999999, 1532E2

REF [126TA5853](#)



- Type: fixed collar
- Thread: M14
- RH/LH: RH
- Pitch: 1,5 mm
- Wrench opening: 19 mm

Used on 1930ES, TOUCAN 8E, TOUCAN 10E

REF [165TA4355](#)

REDUCTOR HUBS



- Gear ratio: 29,8
- Diameter maximum: 265 mm
- Length reductor: 240 mm
- Bolt side 1: 6 x M18 x 1,5 mm
- Bolt side 2: 8 x M16 x 2 mm

Used on 1930ES, 1230ES

REF [165TA4352](#)



Voltage electro motor: 24 VDC, class H, rating AU2500

Used on 1930ES

REF [165TA4356](#)

HUB CAP



- Outer diameter: 56 mm
- Diameter passing: 50,5 mm

Used on 3246E2, 1532E, 1532E3 from serial n° 0200000000 to 0200999999, 1532E2

REF [165TA4353](#)

HUB WHEEL



- Total height: 38
- Conical mounting holes: 27,5-31,5 mm
- Diameter: 140,5 mm
- Number of holes: 5

Used on 600S, 600A from serial n° 0300000000 to 0300099999

REF [165TA4357](#)

TRACKS



- Colour: black
- Width: 400 mm
- Number of links: 82
- Pitch length: 72,5 mm

Used on 3246E2, 1532E3 from serial n° 0200000000 to 0200999999, CM2033, CM1432, 1532E, CM20N, 1532E2

REF [165TA4354](#)



- Colour: non-marking white
- Width: 230 mm
- Number of links: 96
- Pitch length: 39 mm

REF [165TA4358](#)