

# USED ON HAULOTTE



ENGINE PARTS

## COIL PROPORTIONAL VALVES



- Voltage: 12 V
- Height: 76 mm
- Diameter: 70,5 mm

Used on  
HTL3614-3617-4014-401,  
HT43RTJPRO, HT1132RT,  
HT28/85RTJP/PRO,  
HT32RTJPRO, HA100RT,  
HTL3210, HTL3010/3510/4010

REF [138TA7339](#)



- Voltage: 12 VDC
- Height: 76 mm
- Diameter: 72 mm

Used on H125X

REF [138TA7340](#)

## RADIATOR



- Horizontal type
- Length: 401 mm
- Width: 60 mm
- Height: 492 mm

Used on HA120PX

REF [160TA3706](#)




## FILLER CAPS

	Height mm	Outer diameter mm	Inner diameter mm	Used on	REF
	36	60	27	COMPACT10DX, COMPACT12DX	<a href="#">138TA7459</a>
	36	90	27	HAA14TPX, HA16TPX, HA20PX, HA26PX	<a href="#">138TA7462</a>
	40	90	55	HA14TX-16TPX, HB40-4, HA20/260PX, HA61/80J, H21TX/23/25TPX/HB62/68, H25TP, H25TPX, H23(X/P/PX), H16TPX, HB44J, HA80JRT, HA260PX, HA26P, HA20P, HA21T, H21TX	<a href="#">138TA7458</a>
	41,5	50	41,5	HA20PX, HA26PX	<a href="#">128TA3393</a>

## USED ON HAULOTTE



ENGINE PARTS

FILLER CAPS					
	Height mm	Outer diameter mm	Inner diameter mm	Used on	REF
	43	65,5	36	HA15X, HA16P, HA18P, HA16PX, HA16SPX	<a href="#">138TA7463</a>
	62	67	48	H43TPX, HA41PX-NT	<a href="#">138TA7460</a>
	69	95	64,5	HA120PX, H12SX(L), HS5388RT(XL), HA12SD(X/E), H15SD(X/E), H18SDX, H18SX, HS3388RT, H15SX, HS4388RT, HA15D, HA15DX, HA12PX, H12SD(X/E)	<a href="#">138TA7461</a>

FUEL PUMPS					
	Total height mm	Centre distance mm	Number of holes	Used on	REF
	72	78	2		<a href="#">138TA7321</a>
	72	78	2	MJX990, MJX970, MJX950, HTL4017	<a href="#">138TA7322</a>
	90	51	2	H25TPX	<a href="#">138TA7324</a>
	92	45	2	HA120PX	<a href="#">152TA4582</a>

## USED ON HAULOTTE



ENGINE PARTS

FUEL PUMPS					
	Total height mm	Centre distance mm	Number of holes	Used on	REF
	128,5	72,5	2		<a href="#">160TA3360</a>
	130	73	2		<a href="#">138TA7325</a>
	170	73	2	HA18PX, HA51SJRT, HA16/18SPX, HA46/51S, HA14TX-16, HAB40-4, HA16/18PX, HA46/51J, MJ970, HA16X, HA46RT	<a href="#">138TA7323</a>
	257	60	3	HA41/130RTJPRO, HA32RTJPRO, HA100RT, HT43RTJPRO, HT132RT, HTL3210, HTL3614-3617-4014-401, HTL3010/3510/4010, HTL3210,	<a href="#">139TA5153</a>
	112	11	4	H12SX, H15SX	<a href="#">160TA2549</a>

## LIQUID TANKS



- Length: 650 mm
- Height: 500 mm
- Width: 210 mm
- Content: 65 l

Used on HA120PX, H12SX(L), HS5388RT(XL), H12(X/E), H18SDX, H18SX, HS5388RT, H15SX, HS4388RT, HA15D, HA15DX, HA12PX, H12SD(X/E), HAH12SX(L), HS5388RT(XL)

REF [138TA7345](#)



- Length: 585 mm
- Height: 400 mm
- Width: 390 mm
- Content: 75 l

Used on HA16PX, HA18PX, HA16PXNT, HA18PXNT, HA16SPX

REF [160TA2787](#)

# USED ON HAULOTTE



ENGINE PARTS

## ACCELERATOR



- Voltage: 12 V
- Type of current: DC
- Function: pull
- Mounting side: both sides
- Length: 127 mm

Used on HA32PX

REF [138TA7341](#)

## ENGINE STOP SOLENOIDS

	Voltage V	Type of voltage	Function	Mounting side	Length mm	Used on	REF
	12	DC	Push	Both sides	44	H125X	<a href="#">135TA2516</a>
	12	DC	Pull	Both sides	111	H16TPX, HB44J, HA16PXNT, HA46JRT, HA18PXNT, HA51JRT, HA15X	<a href="#">138TA7336</a>
	12	DC	Pull	Both sides	127	H43TPX	<a href="#">138TA7337</a>
	12	DC	Pull	Both sides	71	COMPACT10DX	<a href="#">128TA3249</a>
	12	DC	Pull	Both sides	96	COMPACT10DX	<a href="#">160TA4273</a>
	12	DC	Pull	Without	82,7	H125X, H15SX	<a href="#">160TA1242</a>

# USED ON HAULOTTE



ENGINE PARTS

ENGINE STOP SOLENOIDS							
	Voltage	Type of voltage	Function	Mounting side	Length	Used on	REF
	V				mm		
	12	DC			92,5	HA12DX	<a href="#">165TA3971</a>
	24	DC		Without	127,5	HA16DX, HA20PX	<a href="#">138TA7338</a>
	12	DC	Push	Both sides	69	HA20/260PX, HA61/80J	<a href="#">151TA2997</a>

MUFFLERS	
 <ul style="list-style-type: none"> <li>Length of the muffler: 350 mm</li> <li>Diameter body: 350/180 mm</li> <li>Outer diameter smallest tube: 48 mm</li> <li>Outer diameter biggest tube: 53 mm</li> </ul> <p>Used on HA18PXNT, HA16PXNT, HA20PX</p> <p><b>REF <a href="#">160TA3861</a></b></p>	 <ul style="list-style-type: none"> <li>Length of the muffler: 382 mm</li> <li>Diameter body: 160/96 mm</li> <li>Outer diameter smallest tube: 38 mm</li> <li>Outer diameter biggest tube: 45 mm</li> </ul> <p>Used on HA120PX</p> <p><b>REF <a href="#">160TA2424</a></b></p>
 <ul style="list-style-type: none"> <li>Length of the muffler: 455 mm</li> <li>Diameter body: 177 mm</li> <li>Outer diameter smallest tube: 27 mm</li> <li>Outer diameter biggest tube: 53,4 mm</li> </ul> <p>Used on HA20PX, HA26PX</p> <p><b>REF <a href="#">139TA4587</a></b></p>	 <ul style="list-style-type: none"> <li>Length of the muffler: 575 mm</li> <li>Diameter body: 138/130 mm</li> <li>Outer diameter smallest tube: 48 mm</li> <li>Outer diameter biggest tube: 52 mm</li> </ul> <p>Used on H12SX</p> <p><b>REF <a href="#">160TA1798</a></b></p>

# USED ON HAULOTTE



ENGINE PARTS

## EXHAUST PIPES



- Length: 212 mm
- Outer diameter smallest tube: 51 mm
- Outer diameter biggest tube: 51 mm

Used on H12SD, H18DX, H12SX, H15SD, H15SX, H18SX

**REF [160TA2395](#)**



- Length: 560 mm
- Outer diameter smallest tube: 48 mm
- Outer diameter biggest tube: 48 mm

Used on HA26PX, HA20PX, HA260PX

**REF [160TA3511](#)**



- Length: 670 mm
- Outer diameter smallest tube: 45 mm
- Outer diameter biggest tube: 45 mm

Used on HA18PX, HA51SJRT, HA16/18SPX, HA46/51S, HA16/18PX, HA46/51J,

**REF [139TA3873](#)**



- Length: 720 mm
- Outer diameter smallest tube: 48 mm
- Outer diameter biggest tube: 48 mm

Used on HA15X, HA16X

**REF [160TA2662](#)**

## PARTS EXHAUST



Silencer valve

Used on H21T, HA20P, HA26PX, HA20PX, HA26P, H23T, H25TP, HA260PX, H21TX

**REF [160TA3547](#)**

## OIL DIPSTICKS



- Total length: 292 mm
- Diameter: 12,7 mm
- Length: 215 mm

Used on HA16PX, HA18PX

**REF [160TA2706](#)**



- Total length: 285 mm
- Diameter: 13 mm
- Length: 208 mm

Used on COMPACT12DX

**REF [160TA1143](#)**

# USED ON HAULOTTE



ENGINE PARTS

## TENSIONER BELT



Diameter: 76 mm  
Used on HA16PX, HA16SPX,  
HA16X, HA41PX-NT

**REF [160TA2638](#)**

## TOOTHED BELT



- Timing belt
- Belt width: 25 mm
- Belt height: 5,7 mm
- Pitch: 9,5 mm

Used on HA12PX, HA18PX

**REF [160TA2771](#)**

## V-BELTS



- V-belt, toothed open flank
- Belt width: 10 mm
- Belt height: 7,4 mm
- Outside length: 850 mm

Used on H12DX


**REF [138TA7332](#)**



- V-belt, toothed open flank
- Belt width: 10,1 mm
- Belt height: 8,1 mm
- Outside length: 1125 mm

Used on HA20/260PX,  
HA61/80J, HA18PX, HA51SJRT,  
HA16/18SPX, HA46/51S,  
H14TX-16TPX, HA40-4,  
HA16/18PX, HA46/51J,  
HA16PXNT, HA46JRT,  
HA18PXNT, HA51JRT

**REF [138TA7331](#)**



- V-belt, toothed open flank
- Belt width: 13,5 mm
- Belt height: 10 mm
- Outside length: 1345 mm

Used on H43TPX, HA41PX-NT

**REF [160TA2174](#)**

## FLAT DRIVE BELTS



- Rib width: 2,34 mm
- Belt width: 21,4 mm
- Belt height: 3,5 mm
- Effective length: 914 mm

**REF [138TA7334](#)**



- Rib width: 2,34 mm
- Belt width: 20,6 mm
- Belt height: 3,6 mm
- Effective length: 920 mm

Used on H12SX

**REF [138TA7335](#)**

# USED ON HAULOTTE



ENGINE PARTS

## COUPLINGS



- Biggest diameter: 215,8 mm
- Smallest diameter: 77,8 mm
- Height: 42 mm

Used on HA15X, HA18PX, HA16PX, HA16PXNT, HA18PXNT, HA20P, HA16P, HA18P, HA26PX, HA20PX, HA26P, H16TPX, HA260PX, HA16SPX, HA16X

**REF [138TA7014](#)**



- Biggest diameter: 165,5 mm
- Smallest diameter: 77,8 mm
- Height: 42 mm

Used on H12SD, HA15D, H21T, HA16DX, H18DX, H12SX, H15SD, H23T, H25TP, H15SX, H18SX, HA16D 4X4, HA16D

**REF [138TA7015](#)**

## ALTERNATORS



- Voltage: 12 V
- Current: 55 A

Used on H12SX, HA41, HA43

**REF [103TA3632](#)**



- Voltage: 12 V
- Current: 50 A

Used on H12SX

**REF [138TA7329](#)**



- Voltage: 12 V
- Current: 60 A

Used on HA15X, HA18PX, HA16PX, HA18PXNT, HA16PXNT, H16TPX, HA16SPX, HA16X, HA20PX

**REF [151TA2355](#)**



- Voltage: 12 V
- Current: 95 A

Used on MJX990, HTL4017, MJX970, MJX950

**REF [136TA3822](#)**



- Voltage: 12 V
- Current: 120 A

**REF [152TA9329](#)**



## USED ON HAULOTTE



## STARTERS

ENGINE PARTS



- Voltage: 12 V
- Power: 1,4 kW
- Number of teeth: 9

Used on COMPACT10DX

**REF 160TA5241**

- Voltage: 12 V
- Power: 1,6 kW
- Number of teeth: 9

Used on HA120PX

**REF 135TA5265**

- Voltage: 12 V
- Power: 2 kW
- Number of teeth: 9

Used on H12SDX, H25TPX, HA15DX

**REF 160TA3315**

- Voltage: 12 V
- Power: 2,3 kW
- Number of teeth: 11

Used on H16TPX, HB44J, HA16PXNT, HA46JRT, HA18PXNT, HA51RT, HA15X, HA46JRT

**REF 138TA7326**

- Voltage: 12 V
- Power: 2,45 kW
- Number of teeth: 9

Used on HA16PX, HA16SPX, HA16X, HA20PX

**REF 135TA5465**

- Voltage: 12 V
- Power: 2,7 kW
- Number of teeth: 11

Used on H12SX

**REF 160TA4078**

- Voltage: 12 V
- Power: 3 kW
- Number of teeth: 9

**REF 160TA3172**

- Voltage: 12 V
- Power: 4 kW
- Number of teeth: 9

**REF 160TA4644**