

USED ON UPRIGHT



HYDRAULIC PARTS

LINK STEERING CYLINDERS



- Type: A
- Minimum distance between holes: 78 mm
- Maximum width at the hole: 21 mm
- Total length: 137 mm
- Diameter smallest hole: 17 mm

REF [164TA7599](#)



- Type: B
- Minimum distance between holes: 129 mm
- Maximum width at the hole: 9,8 mm
- Total length: 198,5 mm
- Diameter smallest hole: 22 mm

REF [164TA7606](#)



- Type: B
- Minimum distance between holes: 129 mm
- Maximum width at the hole: 9,8 mm
- Total length: 198,5 mm
- Diameter smallest hole: 22 mm

REF [164TA7607](#)



- Type: B
- Minimum distance between holes: 148 mm
- Maximum width at the hole: 10,4 mm
- Total length: 209 mm
- Diameter smallest hole: 12,7 mm

REF [164TA7598](#)



- Type: C
- Minimum distance between holes: 160 mm
- Maximum width at the hole: 57 mm
- Total length: 127 mm
- Diameter smallest hole: 16 mm

REF [164TA7608](#)

USED ON UPRIGHT



ENGINE PARTS

EXHAUST CLAMP



- Inside clamp diameter: 45 mm
- Length: 43,2 mm

Used on SL20, MX19

REF [155TA1161](#)

FUEL PUMP



- Total height: 90 mm
- Centre distance: 36 mm
- Number of holes: 2

Used on LX31, LX41, LX50, AB46RT, AB46 I/C 2WD, AB46

REF [152TA3228](#)

ENGINE STOP SOLENOIDS



- Voltage: 12 V
- Type of current: DC
- Function: pull
- Mounting side: both sides
- Length: 160,5 mm

REF [122TA7873](#)



- Voltage: 12 V
- Type of current: DC
- Function: pull
- Mounting side: both sides
- Length: 162,5 mm

REF [151TA2316](#)



- Voltage: 12 V
- Type of current: DC
- Function: pull
- Mounting side: both sides
- Length: 59,7 mm

REF [151TA2362](#)



- Voltage: 12 V
- Type of current: DC
- Function: pull
- Mounting side: both sides
- Length: 128,7 mm

REF [135TA2497](#)



- Voltage: 12 V
- Type of current: DC
- Function: pull
- Mounting side: both sides
- Length: 196 mm

REF [122TA7879](#)

USED ON UPRIGHT



ENGINE PARTS

V-BELT



- Belt width string: 10 mm
- Belt height: 7,5 mm
- Outside length: 950 mm

Used on LX31, LX41, LX50, AB46 I/C 2WD, AB46, LX31DD, LX41DD

REF [106TA9059](#)

STARTERS



- Voltage: 12 V
- Power: 1 kW
- Number of teeth: 9

REF [103TA3220](#)



- Voltage: 12 V
- Power: 1 kW
- Number of teeth: 9

REF [164TA7610](#)



- Voltage: 12 V
- Power: 1,4 kW
- Number of teeth: 15

REF [103TA3408](#)



- Voltage: 12 V
- Power: 2,1 kW
- Number of teeth: 10

REF [103TA3314](#)



- Voltage: 24 V
- Power: 1,4 kW
- Number of teeth: 9

REF [165TA4522](#)