

# USED ON UPRIGHT



## WHEELS & TYRES

### CASTORS



- Diameter wheel: 100 mm
- Number of bolt holes: 4
- Width wheel: 50 mm
- Total height: 130 mm

Used on U-DRIVE25, UL II series

**REF [164TA7753](#)**



- Diameter wheel: 102 mm
- Number of bolt holes: 4
- Width wheel: 32 mm
- Total height: 130 mm

Used on UL SERIES

**REF [164TA7752](#)**



- Diameter wheel: 150 mm
- Number of bolt holes: 4
- Width wheel: 50 mm
- Total height: 195 mm

Used on U-DRIVE25, UL II series

**REF [164TA7754](#)**

### HUB WHEELS



- Total height: 56,3 mm
- Conical mounting hole: 38,2-32 mm
- Number of holes: 6

Used on MX50, LX31, LX41

**REF [164TA7242](#)**



- Total height: 38,1 mm
- Conical mounting hole: 31,5-26,95 mm
- Number of holes: 4

Used on X series, SL20, SL20 (12V), X20N, X20W, X26N, X26UN, X32N

**REF [164TA7239](#)**

## USED ON UPRIGHT



LOAD WHEELS					
	Diameter wheel mm	Width wheel mm	Diameter shaft mm	Used on	REF
	254	58,4	19,1	U-DRIVE25, UL II series	<a href="#">151TA2605</a>
	305	100	31,8	MX19	<a href="#">164TA7723</a>
	305	100	31,8	MX19	<a href="#">141TA4894</a>
	305	105	31,7	MX15, MX19	<a href="#">151TA2514</a>
	305	76	44,5	TM12	<a href="#">164TA7728</a>

WHEELS &amp; TYRES

# USED ON UPRIGHT



WHEELS & TYRES

TRACTION WHEELS						
	Diameter wheel	Width wheel	Diameter shaft	Number of bolt holes	Used on	REF
	mm	mm	mm			
	305	100	113	4	MX19	<a href="#">147TA2786</a>
	305	100	28	0	MX19	<a href="#">141TA4895</a>
	305	76	27	2	TM12	<a href="#">129TA9844</a>
	305	76	27	0	TM12, M1230E	<a href="#">145TA9136</a>
	340	102	113	4	MB20/26	<a href="#">129TA8942</a>

# USED ON UPRIGHT



TRACTION WHEELS						
	Diameter wheel	Width wheel	Diameter shaft	Number of bolt holes	Used on	REF
	mm	mm	mm			
	342	102	96	5	MB20/26	<a href="#">129TA9048</a>
	380	127	113	4	SL20	<a href="#">164TA7729</a>
	380	118	86	4	SL20, X series, SL20 (12V), X20N, X20W, X26N, X32N, X26UN	<a href="#">129TA8940</a>
	414	120	86	5	SL20D, SL20	<a href="#">129TA9045</a>
	559	229	110	5	AB38, A38E	<a href="#">164TA7725</a>

WHEELS & TYRES



# USED ON UPRIGHT



## WHEELS & TYRES

### PNEUMATIC TYRES



- Tubeless tyre
- Dimensions: 10 x 16,5

Used on LX50, LX41, LX31, AB46 I/C 2WD, AB46, MX31DD, LX41DD

REF [152TA1854](#)



- Tubeless tyre
- Dimensions: 14 x 17,5

Used on AB46RT, AB46RT 4WD

REF [152TA1859](#)

### WHEEL BOLT



- Length: 38,3 mm
- Thread type: 1/2" UNF
- Imperial pitch: 20 Pi
- RH/LH: RH

Used on LX50, LX31, LX41, XRT27, XRT33, SL26, 30SL, 30RT, SL20D, SL26RT, SL30RT, SL26N, SL30N, SL20 1, 30N, X20N, X20W, X26N

REF [164TA7733](#)

### WHEEL NUT



- Type: cone head
- Thread: 9/16" UNF
- Imperial pitch: 18 Pi
- Wrench opening: 1"

Used on LX50, LX31, LX41, AB46RT European SP, AB46RT Dual fuel, AB46RT, AB46RT 4WD, AB46RTI/C 2WD, AB46, LX31DD, LX41DD, AB46 Electric Bi-energy

REF [104TA9936](#)

## USED ON UPRIGHT



AXLES/PINS			
	Diameter mm	Total length mm	REF
	15,8	56	<a href="#">164TA7001</a>
	19,0	40	<a href="#">164TA7006</a>
	19,0	50	<a href="#">164TA7010</a>
	19,0	57,5	<a href="#">161TA1876</a>
	30,0	185	<a href="#">164TA7005</a>
	31,7	50	<a href="#">164TA7012</a>

HARDWARE

# USED ON UPRIGHT



HARDWARE

## LOCKING PINS



- Diameter pin: 10 mm
- Total length: 63,5 mm

Used on MX19

**REF [164TA7227](#)**



- Diameter pin: 9,5 mm
- Length: 69,8 mm

Used on LX31, LX41, LX50, X20N, X20W, X226N, X26UN, X32N

**REF [164TA7420](#)**



- Diameter pin: 9,4 mm
- Total length: 275 mm
- Length tether: 155 mm

Used on AB85RJ

**REF [164TA7208](#)**



- Diameter pin: 9,5 mm
- Total length: 52 mm

Used on U-DRIVE25, LX50, LX31, LX41, MX15, MX19, SL20, XRT27, XRT33, SL26, 30SL, 30RT, LX31DD, LX41DD, X series, X20N, X20W, X26N, X26UN, X32N, UL II series, X series, SL26RT, SL30RT, SL26N, SL30N, SL26, 30N, LX31DD, LX41DD, SL20, SL14

**REF [164TA7304](#)**