

# USED ON UPRIGHT



ENGINE PARTS

## EXHAUST CLAMP



- Inside clamp diameter: 45 mm
- Length: 43,2 mm

Used on SL20, MX19

**REF [155TA1161](#)**

## FUEL PUMP



- Total height: 90 mm
- Centre distance: 36 mm
- Number of holes: 2

Used on LX31, LX41, LX50, AB46RT, AB46 I/C 2WD, AB46

**REF [152TA3228](#)**

## ENGINE STOP SOLENOIDS



- Voltage: 12 V
- Type of current: DC
- Function: pull
- Mounting side: both sides
- Length: 160,5 mm

**REF [122TA7873](#)**



- Voltage: 12 V
- Type of current: DC
- Function: pull
- Mounting side: both sides
- Length: 162,5 mm

**REF [151TA2316](#)**



- Voltage: 12 V
- Type of current: DC
- Function: pull
- Mounting side: both sides
- Length: 59,7 mm

**REF [151TA2362](#)**



- Voltage: 12 V
- Type of current: DC
- Function: pull
- Mounting side: both sides
- Length: 128,7 mm

**REF [135TA2497](#)**



- Voltage: 12 V
- Type of current: DC
- Function: pull
- Mounting side: both sides
- Length: 196 mm

**REF [122TA7879](#)**

# USED ON UPRIGHT



ENGINE PARTS

## V-BELT



- Belt width string: 10 mm
- Belt height: 7,5 mm
- Outside length: 950 mm

Used on LX31, LX41, LX50, AB46 I/C 2WD, AB46, LX31DD, LX41DD

REF [106TA9059](#)

## STARTERS



- Voltage: 12 V
- Power: 1 kW
- Number of teeth: 9

REF [103TA3220](#)



- Voltage: 12 V
- Power: 1 kW
- Number of teeth: 9

REF [164TA7610](#)



- Voltage: 12 V
- Power: 1,4 kW
- Number of teeth: 15

REF [103TA3408](#)



- Voltage: 12 V
- Power: 2,1 kW
- Number of teeth: 10

REF [103TA3314](#)



- Voltage: 24 V
- Power: 1,4 kW
- Number of teeth: 9

REF [165TA4522](#)