


STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **ALLIS CHALMERS-KALMAR AC**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	74	9	29	230			55-25	119TA7522
	2	76,5	11	33,5	176	V	V	40-10	135TA5625
	2	77	8	28	183			40-10	105TA5001
	2	77	10	31	210			40-10	135TA5339
	2	77	11	34	220		V	40-10	135TA5201
	2	82	8	28	190			40-10	105TA5004
	2	82	9	29	232			40-10	111TA1158
	2	82	9	29	260			50-20	124TA6122
	2	82,5	9	29	195		V	35-05	105TA5007
	2	82,5	9	35	210		V	50-20	124TA6121
	2	95	9	32	315		V	40-10	124TA6088
	2	95	11	38	292		V	40-10	111TA1164



REF [119TA7522](#)



REF [135TA5625](#)



REF [105TA5001](#)



REF [135TA5339](#)



REF [135TA5201](#)



REF [105TA5004](#)



REF [111TA1158](#)



REF [124TA6122](#)



REF [105TA5007](#)



REF [124TA6121](#)



REF [124TA6088](#)



REF [111TA1164](#)




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **ALLIS CHALMERS-KALMAR AC**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	76	9	25	296			05-15-25	107TA9597
	3	88	10	39,5	340	V		35-50-05	135TA5458
	3	88,5	9	29	225		V	40-55-10	105TA4999
	3	88,5	9	29	305			30-45-60	135TA5118
	3	88,5	9	29	305	V		30-45-60	135TA5119
	3	88,5	9	29	305	V		40-55-10	105TA5006
	3	88,5	9	36	306	V		35-05-20	105TA5000
	3	88,5	10	38	345	V		35-50-05	105TA5003
	3	88,5	10	39	310			35-50-05	124TA6065
	3	88,5	10	39	345	V		45-60-15	135TA5123
	3	88,5	10	40	345	V		35-50-05	135TA5381
	3	89	9	29	305	V		35-50-05	135TA5480




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **ALLIS CHALMERS-KALMAR AC**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	89	10	38	340			40-55-10	107TA9581
	3	89	10	39	225	V	V	40-55-10	111TA1186
	3	89	10	40	330			45-60-15	135TA5364
24	2	89	10	40	295		V	50-20	124TA6200
	2	105	11	40	295		V	40-10	124TA6086
	2	105	11	40	330		V	40-10	124TA6087



REF [107TA9581](#)



REF [111TA1186](#)



REF [135TA5364](#)



REF [124TA6200](#)



REF [124TA6086](#)




REF [124TA6087](#)





used for: **ARTISON**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	82,5	9	29	195		V	35-05	135TA5210
	2	95	9	32	235		V	35-05	135TA5172
	2	95	9	32	235		V	40-10	135TA5156




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **AUSA**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	66	9	29	195		V	40-10	135TA5187
	2	74	9	29	213			50-10	136TA3562
	2	77	8	28,3	185			40-10	135TA5554
	2	80	9	29	210			40-10	135TA5165
	2	82	9	24	239	V		55-25	135TA5547
	2	82,2	9	33,4	220	V	V	40-10	135TA5531
	2	82,5	9	29	233			35-05	135TA5551
	3	88,5	10	39	277			55-10-25	135TA5568



REF [135TA5187](#)



REF [136TA3562](#)



REF [135TA5554](#)



REF [135TA5165](#)



REF [135TA5547](#)



REF [135TA5531](#)



REF [135TA5551](#)



REF [135TA5568](#)



STARTERS

Technical drawing of a 3/2-way solenoid valve. The drawing shows the side profile of the valve with dimensions D1, D2, L, and AT-TA. D1 is the total height, D2 is the height of the valve body, L is the length, and AT-TA is the distance from the mounting flange to the center of the valve body.

REF 135TA5277




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **BAUMANN**



voltage (volt)	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	68	11	30	232				135TA5520
	3	89	10	39,5	344			10-40-55	136TA3565




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **BOBCAT**



voltage (volt)	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
U									
12	2	66	9	29	195		V	40-10	135TA5185
	2	66	9	29,3	208			40-10	135TA5404
	2	73,7	12	37	240			40-10	135TA5432
	2	74	9	29	215			45-10	135TA5398
	2	74	13	38	248		V	45-10	135TA5303
	2	77	13	41	240		V	55-25	136TA3491
	2	82,5	9	34	210		V	40-10	135TA5316
	2	82,5	13	46,5	292			35-05	135TA5580
	2	89	10	40	220		V	40-10	135TA5102
	2	95	9	32	285			40-10	135TA5167
	2	95	10	39,6	235		V	40-10	135TA5469
	3	88,5	9	29	305	V		35-55-10	135TA5276



REF [135TA5185](#)



REF [135TA5404](#)



REF [135TA5432](#)



REF [135TA5398](#)



REF [135TA5303](#)



REF [136TA3491](#)



REF [135TA5316](#)



REF [135TA5580](#)



REF [135TA5102](#)



REF [135TA5167](#)



REF [135TA5469](#)




REF [135TA5276](#)

STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **BOBCAT**




voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	88,5	10	36,5	309			45-60-15	135TA5476
	3	88,5	10	38	341	V		40-55-05	103TA3475
	3	88,5	10	39,8	317		V	40-55-10	135TA5470
	3	88,5	10	40	290		V	40-55-10	136TA3458
	3	88,5	12	46	341		V	55-10-25	135TA5382
	3	89	10	32	340		V	55-05-20	136TA3493
	3	89	10	39,7	341	V	V	35-50-05	135TA5557
	3	89	11	40	296	V	V	50-10-25	135TA5564
	3	89	12	46	342		V	55-10-25	135TA5329
	3	92	10	39	308			50-10-25	135TA5348





used for: **BRUNILIFT**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	91	10	33	265			55-10-25	107TA9600



REF [107TA9600](#)




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **BT**




voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	82,5	11	40	295			55-20	106TA8341
	3	89	10	39	360			40-55-10	136TA3460





used for: **CHARLATTE**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	103	10	27	224			30-05-15	135TA5281



REF [135TA5281](#)






STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **CLAAS-UNITRAC**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	88,7	10	39,5	309,2			40-55-10	136TA3511



REF [136TA3511](#)


STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **CLARK-SAMSUNG**




voltage (volt)	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch	reductor	position fixation points LG-BG	reference new
U	AT-BG	D1	AT-TA	D2	L	OLIED	TY-ST	LG-BG	
6	3	88,5	9	36	322			30-45-60	106TA8296
	3	88,5	10	40	327			30-45-60	119TA7508
	3	88,5	13	46	362			30-45-60	106TA8292
12	2	66	9	29	195		V	40-10	124TA6093
	2	66	9	29,3	208			40-10	124TA6196
	2	68	11	29,5	218	V			135TA5536
	2	68	11	30	232				136TA3528
	2	73,2	11	33,5	178	V	V	40-10	135TA5622
	2	73,7	12	37	240			40-10	107TA9588
	2	74	8	28	188			40-10	135TA5197
	2	74	13	38	248		V	45-10	116TA7179
	2	76,5	11	33,5	176	V	V	40-10	135TA5626



STARTERS

For all our latest catalogue updates and company info: www.tvh.com

used for: **CLARK-SAMSUNG**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	77	8	28	183			40-10	105TA5073
	2	77	8	28	190			40-10	105TA5082
	2	77	9	29	192			40-10	105TA5854
	2	77	10	31	210			40-10	135TA5340
	2	77	11	34	210		V	40-10	106TA8324
	2	77	11	34	220		V	40-10	136TA3469
	2	77	11	34	220		V	40-10	105TA5342
	2	77	13	41	240		V	55-25	136TA3490
	2	82	10	39	305	V		35-05	105TA5074
	2	82,5	9	34	210		V	40-10	135TA5314
	2	82,5	9	35	225		V	55-25	124TA6115
	2	82,5	10	40	220		V	40-15	135TA5319




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **CLARK-SAMSUNG**




voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	88,8	10	40	233		V	40-10	135TA5544
	2	89	10	40	187		V	50-20	135TA5131
	2	89	10	40	225		V	50-20	103TA3139
	2	89	10	40	250	V	V	40-10	135TA5321
	2	89	10	40	290		V	40-10	135TA5107
	2	95	9	32	235		V	40-10	135TA5151
	2	95	9	32	285			40-10	105TA5062
	2	95	9	35	228		V	35-05	116TA7162
	2	95	9	35,6	223		V	45-15	116TA7222
	2	95	10	39,6	235		V	40-10	135TA5468
	2	95	15	43,7	224		V	35-05	135TA5448
	2	104	9	25	240			35-05	103TA3138



STARTERS

For all our latest catalogue updates and company info: www.tvh.com

used for: **CLARK-SAMSUNG**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	104	9	25	290			35-05	105TA5066
	3	88,3	12	46,2	403			35-50-05	107TA9590
	3	88,5	9	25	305			30-60-15	105TA5068
	3	88,5	9	29	225		V	40-55-10	135TA5105
	3	88,5	9	29	305			30-45-60	105TA5065
	3	88,5	9	29	305	V		40-55-10	105TA5060
	3	88,5	9	29	305	V		30-45-60	135TA5120
	3	88,5	9	29	305	V		35-55-10	106TA8339
	3	88,5	9	34	295			35-50-05	111TA1182
	3	88,5	9	35	330			40-05-20	103TA3160
	3	88,5	9	36	306	V		35-05-20	136TA3505
	3	88,5	10	26	220			35-50-05	135TA5127



REF [105TA5066](#)



REF [107TA9590](#)



REF [105TA5068](#)



REF [135TA5105](#)



REF [105TA5065](#)



REF [105TA5060](#)



REF [135TA5120](#)



REF [106TA8339](#)



REF [111TA1182](#)



REF [103TA3160](#)



REF [136TA3505](#)



REF [135TA5127](#)




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **CLARK-SAMSUNG**




voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	88,5	10	32	345			50-10-25	106TA8346
	3	88,5	10	36,5	309			45-60-15	135TA5475
	3	88,5	10	38	310	V		35-50-05	116TA7105
	3	88,5	10	38	335			45-60-15	103TA3152
	3	88,5	10	38	341	V		40-55-05	105TA5078
	3	88,5	10	38	345	V		35-50-05	103TA3159
	3	88,5	10	38	350	V		35-50-05	103TA3140
	3	88,5	10	39	277			55-10-25	135TA5565
	3	88,5	10	39	310			35-50-05	103TA3146
	3	88,5	10	39	340	V	V	35-50-10	135TA5328
	3	88,5	10	39	340	V		35-50-10	105TA5061
	3	88,5	10	39	345	V		35-50-05	124TA6079



STARTERS

For all our latest catalogue updates and company info: www.tvh.com

used for: **CLARK-SAMSUNG**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	88,5	10	39	345	V		45-60-15	124TA6070
	3	88,5	10	39	405			55-10-25	135TA5121
	3	88,5	10	40	310	V		35-50-05	103TA3149
	3	88,5	10	40	310	V		35-50-10	103TA3332
	3	88,5	10	40	340		V	55-10-20	116TA7110
	3	88,5	10	40	405	V		55-05-20	103TA3569
	3	88,5	12	46	341		V	55-10-25	106TA8274
	3	88,5	12	46	345			55-10-25	105TA5853
	3	88,6	9	28,8	305			35-05-20	105TA5069
	3	88,7	10	38	346			30-45-60	103TA3153
	3	88,7	10	39,5	309			55-05-25	106TA8257
	3	88,7	10	39,5	309,2			40-55-10	124TA6166




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **CLARK-SAMSUNG**




voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	88,8	10	39,8	367,5			50-05-20	135TA5460
	3	89	9	29	305	V		35-50-05	135TA5481
	3	89	9	36	295			40-05-20	103TA3142
	3	89	10	32	340		V	55-05-20	135TA5322
	3	89	10	38	340			40-55-10	116TA7068
	3	89	10	39	310			50-10-20	103TA3520
	3	89	10	39	360			40-55-10	105TA5067
	3	89	10	39	402			50-05-20	135TA5570
	3	89	10	39,7	341	V	V	35-50-05	135TA5558
	3	89	10	40	340		V	55-10-25	106TA8378
	3	89	11	40	296	V	V	50-10-25	119TA7514
	3	89	11	40	315			40-05-20	124TA6094



STARTERS

For all our latest catalogue updates and company info: www.tvh.com

used for: **CLARK-SAMSUNG**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	89	12	46	342		V	55-10-25	105TA5076
	3	91	10	40	395			40-60-20	103TA3136
	3	92	11	55	460			30-55-05	103TA3485
	3	103,5	10	28	225			30-05-00	106TA8396
24	2	82	11	41	250	V	V	40-10	116TA7118
	2	82	11	41,5	250		V	40-10	105TA5080
	3	89	9	34	370			35-55-10	103TA3162
	3	89	10	40	315			50-10-20	135TA5634



REF [105TA5076](#)



REF [103TA3136](#)



REF [103TA3485](#)



REF [106TA8396](#)



REF [116TA7118](#)



REF [105TA5080](#)



REF [103TA3162](#)



REF [135TA5634](#)




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **COVENTRY CLIMAX**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	77	8	28	183			40-10	119TA7501
	2	82	8	28	190			40-10	105TA5086
	2	95	9	32	210		V	40-10	105TA5092
	2	95	9	32	230		V	40-10	135TA5166
	2	95	9	32	305			40-10	105TA5091
	3	0	11	28,5	237	V		40-50-05	106TA8392
	3	65	12	32	222			35-50-05	103TA3578
	3	74	9	29	210		V	40-50-10	105TA5093
	3	74	9	29	230		V	40-50-10	105TA5085
	3	88,5	9	29	305			30-45-60	124TA6068
	3	88,5	9	29	305	V		40-55-10	105TA5084
	3	88,7	10	39,5	309,2			40-55-10	124TA6164






STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **COVENTRY CLIMAX**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	89	10	39	310			50-10-20	105TA5087
	3	89	10	39	360			40-55-10	105TA5083
	3	92	9	36	310	V		40-55-10	135TA5578
24	3	88,5	10	39	365	V		40-55-05	119TA7509



STARTERS




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **DESTA**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	76	9	29	260			55-25	105TA5101




REF [105TA5101](#)





used for: **DIECI**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	110	9	34	340			35-50-05	135TA5139



REF [135TA5139](#)




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **FANTUZZI**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	110	9	34	300			35-45-05	135TA5374
	3	110	9	34	340			35-50-05	135TA5138
	3	110	9	34	340			50-05-20	135TA5278
	3	110	9	34,5	338			35-50-05	135TA5376
24	3	88,5	11	40	385			50-10-25	135TA5345
	3	88,5	11	40	405			50-10-25	135TA5269
	3	88,7	10	32	340	V	V	50-10-20	136TA3486
	3	88,7	11	40,7	404			50-05-25	135TA5392
	3	89	9	34	385			55-05-20	135TA5361
	3	91,7	12	46	475			30-50-05	135TA5391
	3	92	11	55	358			45-05-25	135TA5574
	3	92	11	56	480			35-55-15	135TA5106




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **FENWICK & PEG**




voltage (volt)	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch	reductor	position fixation points LG-BG	reference new
U						OLIED	TY-ST		
12	2	82	9	25	293				106TA8261
	2	82	9	29	280			50-20	105TA5103
	2	82	9	34	295			55-25	107TA9575
	2	82	9	36,5	291,5			50-20	106TA8259
	2	82,5	9	30	291			55-25	103TA3541
	3	65	10	27	262			40-55-05	135TA5400
	3	66	9	25	195			55-10-25	103TA3163
	3	82	9	25	265			35-05-20	105TA5107
	3	82	11	29	225			35-50-05	135TA5128
	3	82,5	9	25	225			35-05-20	105TA5106
	3	88,4	10	39,2	306	V		50-10-20	135TA5510
	3	88,5	9	29	305	V		40-55-10	105TA5108



STARTERS

For all our latest catalogue updates and company info: www.tvh.com

used for: **FENWICK & PEG**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	88,5	9	34	295			50-05-20	124TA6177
	3	88,5	9	34	295			35-50-05	135TA5192
	3	88,5	10	26	220			35-50-05	103TA3169
	3	88,5	10	40	295			55-10-20	103TA3367
	3	88,5	10	40	315			55-10-20	105TA5110
	3	88,5	10	40	325			50-10-20	103TA3168
	3	89	10	39	310			50-10-20	135TA5600
	3	89	10	39	360			40-55-10	105TA5104
	3	110	9	34	340			35-50-05	116TA7101
24	3	88,5	9	34	415			35-55-05	106TA8270
	3	88,8	10	39	340			35-55-05	135TA5591



REF [124TA6177](#)



REF [135TA5192](#)



REF [103TA3169](#)



REF [103TA3367](#)



REF [105TA5110](#)



REF [103TA3168](#)



REF [135TA5600](#)



REF [105TA5104](#)



REF [116TA7101](#)



REF [106TA8270](#)



REF [135TA5591](#)




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **GENIE**



voltage (volt)	number of fixation points	flange dia. (mm)	number of teeth	gear dia. (mm)	total length (mm)	wet clutch	reductor	position fixation points	reference new
U	AT-BG	D1	AT-TA	D2	L	OLIED	TY-ST	LG-BG	
12	2	65,8	9	29,2	189			40-10	135TA5446
	2	82,5	9	33,7	250			30-05	136TA3552
	2	82,5	9	34	255			35-05	135TA5466
	3	82	11	35	292			30-35-05	135TA5371






STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **HAKO**



voltage (volt)	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	66	9	0	231			40-10	135TA5467



REF [135TA5467](#)




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **HANGZHOU / HC / HANGCHA**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	73,3	9	28,5	206,5			40-10	136TA3555
	2	74	9	28,8	208			40-10	136TA3566
	2	82	8	28	190			40-10	135TA5218
	2	82	11	39	300	V	V	50-25	135TA5594
	2	82,5	9	29	195		V	35-05	135TA5211
	2	95	9	32	227		V	35-05	135TA5636
	2	95	9	32	235		V	35-05	135TA5173
	2	95	9	32	235		V	40-10	135TA5157
	2	95	9	32	305			40-10	135TA5176
	2	95	9	34,8	255		V	35-05	135TA5644
	2	95	9	35	224		V	50-20	135TA5427
24	3	105	11	40	304		V	40-55-10	135TA5291






STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **HANGZHOU / HC / HANGCHA**




voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
24	3	105	11	40	339		V	45-05-15	135TA5234



REF [135TA5234](#)



used for: **HARLAN**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	88,5	10	39	405			55-10-25	135TA5122
	3	88,5	10	40	340		V	55-10-20	135TA5162
	3	103,5	10	28	225			30-05-00	135TA5410






STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **HAULOTTE**



voltage (volt)	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
U									
12	2	76	9	29	234			40-10	135TA5537
	2	76	9	29	260			50-20	135TA5265
24	2	82,5	11	40	340			55-25	135TA5292




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **HELI**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	82	8	28	190			40-10	135TA5219
	2	82	9	29	210	V	V	40-10	135TA5216
	2	82,5	9	29	195		V	35-05	135TA5214
	2	82,5	9	33,5	220	V	V	40-10	135TA5493
	2	95	9	32	235		V	40-10	135TA5159
	2	95	9	32,5	225		V	35-05	135TA5631
24	3	105	11	40	357		V	35-50-10	136TA3484




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **HYSTER**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
6	3	88,5	9	36	322			30-45-60	106TA8294
	3	88,5	10	40	327			30-45-60	106TA8286
	3	88,5	13	46	362			30-45-60	106TA8290
12	2	55	9	29	210		V	45-10	135TA5434
	2	55	10	32	210		V	50-20	135TA5351
	2	68	11	30	232				135TA5522
	2	70	9	29	220			55-25	135TA5372
	2	73,2	11	33,5	178	V	V	40-10	135TA5620
	2	73,7	12	37	240			40-10	135TA5429
	2	74	8	28	188			40-10	116TA7116
	2	74	8	28	194			40-10	107TA9584
	2	74	9	28,8	187,5		V	50-15	119TA7526



REF [106TA8294](#)



REF [106TA8286](#)



REF [106TA8290](#)



REF [135TA5434](#)



REF [135TA5351](#)



REF [135TA5522](#)



REF [135TA5372](#)



REF [135TA5620](#)



REF [135TA5429](#)



REF [116TA7116](#)



REF [107TA9584](#)



REF [119TA7526](#)




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **HYSTER**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	74	9	29	190	V	V	50-20	135TA5353
	2	74	9	29	215			45-10	135TA5396
	2	74	9	29	250			55-25	135TA5249
	2	76,5	11	33,5	176	V	V	40-10	135TA5623
	2	77	8	28,3	185			40-10	135TA5552
	2	77	10	31	210			40-10	135TA5337
	2	80	9	29	210			40-10	135TA5163
	2	82	8	28	190			40-10	136TA3475
	2	82	9	24	239	V		55-25	135TA5548
	2	82	9	25	213			55-20	135TA5483
	2	82	10	39	305	V		35-05	135TA5091
	2	82,5	9	25	285	V		55-25	105TA5136



REF [135TA5353](#)



REF [135TA5396](#)



REF [135TA5249](#)



REF [135TA5623](#)



REF [135TA5552](#)



REF [135TA5337](#)



REF [135TA5163](#)



REF [136TA3475](#)



REF [135TA5548](#)



REF [135TA5483](#)



REF [135TA5091](#)



REF [105TA5136](#)




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **HYSTER**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	82,5	9	29	195		V	35-05	136TA3472
	2	82,5	9	29	230			55-25	116TA7147
	2	82,5	9	29	233			35-05	135TA5550
	2	82,5	9	30	320			40-10	136TA3498
	2	82,5	9	35	210		V	50-20	135TA5225
	2	82,5	9	35	225		V	55-25	135TA5217
	2	82,5	10	38	258	V	V	55-25	135TA5393
	2	82,5	10	38,5	288			50-20	124TA6142
	2	82,5	10	40	220		V	40-15	135TA5317
	2	82,5	11	34	230		V	55-25	135TA5235
	2	89	10	40	220		V	40-10	135TA5101
	2	89	10	40	250	V	V	40-10	124TA6152



REF [136TA3472](#)



REF [116TA7147](#)



REF [135TA5550](#)



REF [136TA3498](#)



REF [135TA5225](#)



REF [135TA5217](#)



REF [135TA5393](#)



REF [124TA6142](#)



REF [135TA5317](#)



REF [135TA5235](#)



REF [135TA5101](#)



REF [124TA6152](#)




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **HYSTER**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	89	10	40	290		V	40-10	136TA8302
	2	89	10	40,3	300		V	50-20	135TA5562
	2	89	13	39	295	V	V	50-20	135TA5605
	2	89,6	11	40	295	V	V	40-10	135TA5423
	2	90	11	40	290	V	V	45-10	135TA5330
	2	95	9	32	235		V	40-10	103TA3198
	2	95	9	32	235		V	35-05	105TA5147
	2	95	9	32,5	230		V	40-10	106TA8275
	2	95	9	35	224		V	50-20	135TA5425
	2	95	9	35	228		V	35-05	135TA5584
	2	95	11	38	292		V	40-10	135TA5283
	2	95	11	43,2	317		V	45-15	135TA5505




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **HYSTER**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	104	9	25	290			35-05	135TA5112
	3	74	9	29	210		V	40-50-10	135TA5097
	3	74	9	29	230		V	40-50-10	135TA5099
	3	76	9	25	296			05-15-25	107TA9596
	3	88	10	39,5	340	V		35-50-05	103TA3182
	3	88,5	9	29	225		V	40-55-10	135TA5103
	3	88,5	9	29	305			30-45-60	136TA3461
	3	88,5	9	29	310			35-50-05	116TA7108
	3	88,5	9	34	295			35-50-05	135TA5190
	3	88,5	9	36	305			35-50-05	136TA3462
	3	88,5	10	38	310	V		35-50-05	135TA5144
	3	88,5	10	39	305	V		55-10-25	105TA5146



REF [135TA5112](#)



REF [135TA5097](#)



REF [135TA5099](#)



REF [107TA9596](#)



REF [103TA3182](#)



REF [135TA5103](#)



REF [136TA3461](#)



REF [116TA7108](#)



REF [135TA5190](#)



REF [136TA3462](#)



REF [135TA5144](#)



REF [105TA5146](#)




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **HYSTER**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	88,5	10	39	310			35-50-05	135TA5111
	3	88,5	10	39	340	V	V	35-50-10	135TA5326
	3	88,5	10	39	345	V		35-50-05	105TA5144
	3	88,5	10	40	290		V	40-55-10	135TA5100
	3	88,5	10	40	305	V		35-50-05	116TA7106
	3	88,5	10	40	310	V		35-50-05	135TA5113
	3	88,5	10	40	340		V	55-10-20	103TA3199
	3	88,5	10	40	345	V		35-50-05	135TA5379
	3	88,5	12	46	345			55-10-25	105TA5859
	3	88,7	10	39	405			50-05-25	105TA5131
	3	88,7	10	39,5	309,2			40-55-10	136TA3507
	3	88,8	10	40	285	V	V	40-55-10	105TA5886




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **HYSTER**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	88,8	13	45,5	307			40-55-10	135TA5462
	3	89	9	29	305			35-50-05	105TA5142
	3	89	10	39	310			50-10-20	135TA5124
	3	89	10	39	350	V		55-10-25	103TA3404
	3	89	10	39	360			40-55-10	116TA7078
	3	89	10	40	290		V	55-10-25	135TA5094
	3	89	10	40	340		V	55-10-25	103TA3154
	3	89	10	40	341	V	V	55-10-25	106TA8317
	3	89	10	40,5	293		V	40-55-10	136TA3546
	3	89	13	45,7	307			55-10-25	135TA5362
	3	89,5	10	32	305	V		55-10-25	105TA5141
	3	91,8	12	46,5	475			35-50-10	107TA9613




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **HYSTER**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	92	10	39	308			50-10-25	135TA5346
	3	92	11	56	530			50-10-25	105TA5132
	3	92	12	46	460			35-50-10	103TA3191
	3	100	13	51	240		V	50-05-20	105TA5145
	3	100	13	51	275		V	55-10-25	135TA5302
24	2	82	11	41	250	V	V	40-10	136TA3468
	2	82,5	10	38	288		V	50-20	135TA5293
	2	82,5	10	39	290		V	40-10	135TA5298
	2	89	10	40	295		V	50-20	135TA5517
	2	89,6	9	31,5	284		V	50-20	106TA8263
	2	90	9	32	315			55-25	105TA5140
	2	90	11	40	295	V	V	45-10	135TA5243






STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **HYSTER**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
24	2	105	11	40	295		V	50-20	135TA5237
	2	105	11	40	295		V	40-10	135TA5177
	3	88,5	10	40	341		V	55-10-20	135TA5534
	3	88,8	10	39	340			35-55-05	135TA5588
	3	88,8	10	39,5	401			50-05-20	135TA5507
	3	92	11	55,5	414	V	V	45-05-25	135TA5541
	3	92	12	46	407			50-05-25	136TA3563
	3	92	12	46	458			50-05-25	105TA5139
	3	105	11	40	370			40-55-10	135TA5267




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **HYUNDAI**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	77	8	26	188			40-10	124TA6208
	2	77	8	27	220			40-10	135TA5593
	2	77	10	31	210			40-10	124TA6158
	2	81,5	11	39	307			55-25	136TA3533
	2	82	8	28	190			40-10	108TA8856
	2	82,5	9	33,5	220	V	V	40-10	135TA5492
	2	89	10	40	187		V	50-20	105TA5125
	2	89	10	40	225		V	50-20	135TA5110
	2	89	10	40	290		V	40-10	107TA9582
	2	95	9	32	210		V	40-10	135TA5496
	2	95	9	32	235		V	40-10	106TA8362
	2	95	9	35	228		V	35-05	116TA7163



REF [124TA6208](#)



REF [135TA5593](#)



REF [124TA6158](#)



REF [136TA3533](#)



REF [108TA8856](#)



REF [135TA5492](#)



REF [105TA5125](#)



REF [135TA5110](#)



REF [107TA9582](#)



REF [135TA5496](#)



REF [106TA8362](#)




REF [116TA7163](#)

STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **HYUNDAI**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	95	11	38	292		V	40-10	105TA5127
	3	90	13	39	295		V	50-05-15	135TA5389
	3	100	9	34,8	239		V	40-55-10	135TA5514
24	2	82,5	10	38,5	253	V	V	55-25	136TA3557
	2	95	11	40	275		V	40-10	107TA9555
	2	105	11	40	295		V	40-10	105TA5128
	3	60	9	35	240		V	40-60-10	136TA3502
	3	88,4	9	33,5	345,5			35-55-05	116TA7236
	3	88,7	10	32	340	V	V	50-10-20	136TA3487
	3	88,8	10	39,5	401			50-05-20	135TA5508
	3	92	11	56	480			35-55-15	124TA6063
	3	105	11	40	345		V	35-50-10	105TA5123



REF [105TA5127](#)



REF [135TA5389](#)



REF [135TA5514](#)



REF [136TA3557](#)



REF [107TA9555](#)



REF [105TA5128](#)



REF [136TA3502](#)



REF [116TA7236](#)



REF [136TA3487](#)



REF [135TA5508](#)



REF [124TA6063](#)




REF [105TA5123](#)





used for: **IRISMAN**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	82,5	9	29	195		V	35-05	135TA5213




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **JCB**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	74	9	29	210			40-10	135TA5472
	2	89	13	39	295	V	V	50-20	135TA5607
	3	88,5	10	39,5	277			40-50-10	135TA5572
	3	88,7	10	39,5	309,2			40-55-10	136TA3509
	3	88,8	10	40,4	270			35-55-10	135TA5637
	3	88,8	11	41,4	347			35-05-20	135TA5608
	3	89	10	32	340		V	55-05-20	135TA5324
	3	101,4	10	39,6	308	V		55-10-25	135TA5640
24	2	95	9	35	246		V	35-05	136TA3569
	2	95	9	35	312			35-05	135TA5384
	3	91,5	12	45,8	414			30-50-10	136TA3567
	3	105	11	40	345		V	35-50-10	135TA5385




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **JLG**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	66	9	29	195		V	40-10	136TA3465
	2	80	8	28	192			35-05	135TA5474
	2	82,5	9	34	255			35-05	135TA5465
	2	82,5	9	35	290			50-20	135TA5359
	3	82	11	35	292			30-35-05	135TA5370
	3	88,4	10	39,2	306	V		50-10-20	135TA5512
24	2	82,5	9	34	319			35-05	136TA3561




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **JUNGHEINRICH-STEINBOCK**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	68	11	0	233				135TA5587
	2	68	11	29	245				135TA5519
	2	73,7	12	37	240			40-10	135TA5431
	2	74	8	28	188			40-10	105TA5157
	2	74	8	28	194			40-10	135TA5402
	2	74	9	29	215			45-10	106TA8385
	2	74	9	30	188			40-10	135TA5367
	2	74	11	34	228		V	45-15	116TA7177
	2	74	13	38	248		V	45-10	116TA7180
	2	76	9	33	284			35-05	135TA5526
	2	77	13	41	240		V	55-25	135TA5308
	2	82	8	28	190			40-10	124TA6118




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **JUNGHEINRICH-STEINBOCK**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	82	10	31	278	V		40-10	135TA5530
	2	82,5	9	25	275	V		50-20	135TA5261
	2	82,5	9	25	292				135TA5439
	2	82,5	9	30	291			55-25	105TA5152
	2	82,5	10	38	258	V	V	55-25	135TA5395
	2	95	9	32	305			40-10	111TA1184
	3	74	9	29	210		V	40-50-10	135TA5369
	3	76	10	26,5	240			50-10-20	116TA7237
	3	76	10	26,5	243			40-55-10	106TA8391
	3	82,5	9	25	320			40-55-20	135TA5471
	3	88,5	9	29	252			40-50-05	116TA7197
	3	88,5	10	39	335			55-15-25	105TA5254




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **JUNGHEINRICH-STEINBOCK**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	89	10	27	252			40-50-05	135TA5479
	3	89	13	45,7	307			55-10-25	135TA5363
	3	89	13	46	308			40-55-10	116TA7206
	3	100	12	48	305			55-10-25	105TA5154
	3	100	13	51	240		V	50-05-20	105TA5160
	3	100	13	51	264		V	55-10-25	105TA5149
	3	100	13	51	265		V	55-10-25	105TA5150
	3	100	13	51	275		V	55-10-25	105TA5158
24	2	105	11	40	346			40-10	106TA8401
	3	92	12	45	365			40-60-20	135TA5289



REF [135TA5479](#)



REF [135TA5363](#)



REF [116TA7206](#)



REF [105TA5154](#)



REF [105TA5160](#)



REF [105TA5149](#)



REF [105TA5150](#)



REF [105TA5158](#)



REF [106TA8401](#)



REF [135TA5289](#)

