


STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **KALMAR**



voltage (volt)	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch	reductor	position fixation points LG-BG	reference new
U	AT-BG	D1	AT-TA	D2	L	OLIED	TY-ST	LG-BG	
12	3	82	11	35	292			30-35-05	105TA5169
	3	88,8	10	39,8	367,5			50-05-20	135TA5461
	3	89	10	40	347			50-10-25	136TA3554
	3	89	13	45,7	307			55-10-25	116TA7208
	3	89,5	10	38	339			55-10-25	135TA5420
24	2	89	10	40	295		V	50-20	136TA3526
	3	88,5	11	40	385			50-10-25	103TA3482
	3	88,5	11	40	405			50-10-25	107TA9570
	3	88,7	11	40,7	404			50-05-25	105TA5167
	3	89	9	34	338			35-50-05	116TA7218
	3	89	9	34	340			35-50-10	124TA6132
	3	89	9	34	345			35-50-10	135TA5286




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **KALMAR**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
24	3	89	9	34	385			55-05-20	136TA3499
	3	89	10	40,4	294,5		V	40-55-10	135TA5639
	3	89	11	39,3	295	V	V	40-50-20	135TA5577
	3	89	12	43	321	V		35-50-05	135TA5641
	3	92	11	55	358			45-05-25	135TA5576
	3	92	11	56	496			35-55-15	136TA3545




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **KOMATSU**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	68	11	0	233				135TA5586
	2	70	8	29	215			30-05	105TA5196
	2	70	9	26	238			50-15	106TA8337
	2	70	9	29	220			55-25	105TA5174
	2	73,7	12	37	240			40-10	105TA5222
	2	74	9	29	190	V	V	50-20	105TA5223
	2	74	9	29	215			45-10	106TA8383
	2	74	9	29	230			55-25	116TA7151
	2	74	9	29	250			55-25	135TA5251
	2	74	13	38	248		V	45-10	106TA8321
	2	77	8	28	183			40-10	136TA3471
	2	77	11	34	220		V	40-10	136TA3470




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **KOMATSU**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	80	8	28	192			35-05	136TA3523
	2	80	9	29	210			40-10	105TA5185
	2	82	8	27	185			35-05	106TA5116
	2	82	8	28	190			40-10	105TA5217
	2	82	8	29	210			55-25	116TA7140
	2	82	8	29	235			40-10	135TA5230
	2	82	9	29	210	V	V	40-10	124TA6113
	2	82	9	29	232			40-10	135TA5342
	2	82	9	29	260			50-20	105TA5199
	2	82	9	29	313			55-25	105TA5192
	2	82,5	9	29	195		V	35-05	106TA5128
	2	82,5	9	29	221,5			55-25	105TA5221



REF [136TA3523](#)



REF [105TA5185](#)



REF [106TA5116](#)



REF [105TA5217](#)



REF [116TA7140](#)



REF [135TA5230](#)



REF [124TA6113](#)



REF [135TA5342](#)



REF [105TA5199](#)



REF [105TA5192](#)



REF [106TA5128](#)



REF [105TA5221](#)




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **KOMATSU**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	82,5	9	29	230			55-25	105TA5215
	2	82,5	9	34	210		V	40-10	105TA5214
	2	82,5	9	35	210		V	50-20	116TA7137
	2	82,5	9	35	225		V	55-25	105TA5220
	2	82,5	9	35	245		V	35-05	106TA8320
	2	82,5	9	35	285			35-05	106TA5130
	2	82,5	11	34	225		V	35-05	105TA5202
	2	83,3	9	29,2	210		V	35-05	135TA5453
	2	88,5	9	29	220			40-10	107TA9576
	2	89	10	40	187		V	50-20	116TA7099
	2	94,5	9	32,5	230		V	40-10	107TA9609
	2	95	9	29	220			40-05	105TA5180




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **KOMATSU**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	95	9	32	210		V	40-10	105TA5187
	2	95	9	32	210		V	40-10	105TA5175
	2	95	9	32	210		V	35-05	103TA3217
	2	95	9	32	230		V	40-10	105TA5219
	2	95	9	32	230		V	40-10	107TA9579
	2	95	9	32	233		V	40-10	135TA5336
	2	95	9	32	235		V	40-10	105TA5863
	2	95	9	32	235		V	35-05	105TA5182
	2	95	9	32	285			40-10	136TA3463
	2	95	9	32	285			40-10	105TA5186
	2	95	9	32	305			40-10	105TA5209
	2	95	9	32	315		V	40-10	105TA5207



REF [105TA5187](#)



REF [105TA5175](#)



REF [103TA3217](#)



REF [105TA5219](#)



REF [107TA9579](#)



REF [135TA5336](#)



REF [105TA5863](#)



REF [105TA5182](#)



REF [136TA3463](#)



REF [105TA5186](#)



REF [105TA5209](#)



REF [105TA5207](#)




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **KOMATSU**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	95	9	32	317	V	V	40-10	105TA5173
	2	95	9	32	321,5	V	V	40-10	105TA5195
	2	95	9	32,5	188		V	40-10	116TA7235
	2	95	9	32,5	230		V	40-10	106TA8276
	2	95	9	35	224		V	50-20	106TA5126
	2	95	9	35	228		V	35-05	124TA6137
	2	95	9	35,5	222			40-10	105TA5190
	2	95	11	34	188	V	V	40-10	106TA8249
	2	95	11	38	292		V	40-10	119TA7502
	2	95	11	38,2	295	V	V	40-10	105TA5203
	2	95	15	44	233,5		V	35-05	136TA3520
	2	95	15	44	290		V	40-10	136TA3535




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **KOMATSU**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	74	9	29	210		V	40-50-10	106TA8298
	3	76	10	26,5	240			50-10-20	135TA5433
	3	82	11	29	225			35-50-05	116TA7094
	3	82,5	10	27	260			35-50-05	116TA7100
	3	88,5	9	29	252			40-50-05	106TA8310
	3	88,5	10	39	335			55-15-25	106TA8338
	3	88,7	10	39,5	309,2			40-55-10	124TA6168
	3	88,7	10	39,5	334			40-55-25	105TA5860
	3	89	10	39	225	V	V	40-55-10	124TA6091
	3	89	10	39	310			50-10-20	106TA8375
	3	89	10	39	360			40-55-10	106TA8379
	3	89	10	40	339,3			50-05-20	135TA5487




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **KOMATSU**



voltage (volt)	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch	reductor	position fixation points LG-BG	reference new
U	AT-BG	D1	AT-TA	D2	L	OLIED	TY-ST	LG-BG	
12	3	89	13	45,7	307			55-10-25	106TA8303
	3	89	13	46	308			40-55-10	136TA3500
	3	92	10	39	308			50-10-25	107TA9565
	3	92	10	39	310			50-10-20	106TA8357
	3	92	12	46	460			35-50-10	106TA8363
	3	100	13	51	240		V	50-05-20	116TA7171
	3	105	11	40	295		V	35-50-10	105TA5183
	3	105	11	40	340	V	V	35-50-05	105TA5218
	3	110	9	34	295			35-50-05	116TA7095
	3	110	9	34	295			50-05-20	116TA7103
	3	110	9	34,5	338			35-50-05	116TA7217
24	2	82,5	9	35	242		V	35-05	116TA7125



REF [106TA8303](#)



REF [136TA3500](#)



REF [107TA9565](#)



REF [106TA8357](#)



REF [106TA8363](#)



REF [116TA7171](#)



REF [105TA5183](#)



REF [105TA5218](#)



REF [116TA7095](#)



REF [116TA7103](#)



REF [116TA7217](#)




REF [116TA7125](#)

STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **KOMATSU**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
24	2	89	10	40	295		V	50-20	106TA8398
	2	94,5	9	35	329		V	40-10	135TA5516
	2	95	9	32,5	230		V	40-10	106TA5125
	2	95	9	35	312			35-05	105TA5178
	2	95	9	35	325		V	40-10	103TA3422
	2	95	9	35	330		V	40-10	105TA5204
	2	95	9	35	330		V	40-10	105TA5862
	2	95	9	35	333		V	40-10	107TA9598
	2	100	12	45	266		V	45-15	135TA5325
	2	104,7	11	40,3	375		V	40-10	107TA9615
	2	105	11	40	295		V	40-10	135TA5179
	2	105	11	40	330		V	40-10	105TA5208



REF [106TA8398](#)



REF [135TA5516](#)



REF [106TA5125](#)



REF [105TA5178](#)



REF [103TA3422](#)



REF [105TA5204](#)



REF [105TA5862](#)



REF [107TA9598](#)



REF [135TA5325](#)



REF [107TA9615](#)



REF [135TA5179](#)



REF [105TA5208](#)




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **KOMATSU**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
24	2	105	11	40	338		V	40-10	105TA5200
	2	105	11	40	338		V	40-10	103TA3518
	3	88,5	10	37,5	316,5		V	50-05-25	135TA5497
	3	88,8	10	39	340			35-55-05	135TA5590
	3	92	10	40	315	V	V	30-50-10	135TA5609
	3	92	11	0	450			35-55-10	107TA9601
	3	92	11	56	410		V	35-50-10	105TA5211
	3	92	12	45	412		V	30-50-10	105TA5205
	3	99,5	12	46	368			35-50-10	106TA8403
	3	100	13	40	370			35-50-10	106TA8402
	3	100	13	46	363			35-50-10	105TA5210
	3	100	13	46	365			35-50-10	105TA5193




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **KOMATSU**




voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
24	3	100	13	46	370		V	35-50-10	103TA3491
	3	100	13	46	410		V	35-50-10	105TA5213
	3	100	13	46	455		V	35-50-10	105TA5212
	3	100	13	46,5	445			50-10-25	135TA5451
	3	104,7	11	40,3	345		V	40-50-10	107TA9616
	3	105	11	40	305		V	35-50-05	105TA5179
	3	105	11	40	345		V	35-50-05	124TA6085
	3	105	11	40	345		V	35-50-10	124TA6178
	3	105	11	40	346		V	35-55-10	105TA5188
	3	105	11	40	346			35-50-05	116TA7169
	3	105	11	40	351			30-55-05	105TA5189
	3	105	11	40	365			35-50-10	105TA5198





used for: **KOMATSU**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
24	3	105	11	40,5	287		V	30-55-10	135TA5502
	3	121,5	11	48,3	450			50-05-25	107TA9603



REF [135TA5502](#)



REF [107TA9603](#)




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **KOOI AAP**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	65,8	9	29,2	189			40-10	135TA5444
	2	66	9	29	195		V	40-10	124TA6092
	2	66	9	29,3	208			40-10	135TA5405




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **LINDE-LANSING**




voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	73,7	12	37	240			40-10	135TA5428
	2	74	13	38	248		V	45-10	135TA5304
	2	76	9	25	256			35-05	106TA8388
	2	76	9	25	265			35-05	106TA8356
	2	76	10	27	257			50-20	135TA5630
	2	76	10	27,6	257			50-20	135TA5473
	2	76	10	27,8	244			55-25	136TA3544
	2	76	11	28,8	239			55-25	136TA3564
	2	77	8	28	183			40-10	124TA6106
	2	77	8	28	190			40-10	124TA6096
	2	77	10	31	210			40-10	107TA9406
	2	77	11	34	220		V	40-10	124TA6104



STARTERS

For all our latest catalogue updates and company info: www.tvh.com

used for: **LINDE-LANSING**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	82	8	28	190			40-10	111TA1181
	2	82	9	29	210	V	V	40-10	124TA6112
	2	82	9	29	280			50-20	106TA8373
	2	82,5	9	25	255			55-25	106TA8340
	2	82,5	9	29	195		V	35-05	124TA6108
	2	82,5	9	35	210		V	50-20	124TA6120
	2	89	10	40	187		V	50-20	135TA5134
	2	95	9	32,5	188		V	40-10	136TA3517
	2	95	9	35	228		V	35-05	124TA6135
	3	65	10	27	262			40-55-05	109TA5992
	3	65	13	32	190			35-50-05	135TA5386
	3	67	9	25	197			55-10-25	136TA8303




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **LINDE-LANSING**




voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	82	9	25	265			35-05-20	105TA5236
	3	82	11	29	225			35-50-05	135TA5129
	3	82,5	9	25	223			55-10-25	106TA8266
	3	82,5	9	25	225			35-05-20	106TA8376
	3	82,5	9	25	225			35-05-20	116TA7164
	3	82,5	10	27	260			35-50-05	135TA5135
	3	88,4	10	39,2	306	V		50-10-20	135TA5511
	3	88,5	9	29	305			30-45-60	105TA5232
	3	88,5	9	34	295			35-50-05	105TA5235
	3	88,5	9	34	295			50-05-20	124TA6176
	3	88,5	9	34	302,5			40-50-10	135TA5538
	3	88,5	10	39	277			55-10-25	136TA3531



STARTERS

For all our latest catalogue updates and company info: www.tvh.com

used for: **LINDE-LANSING**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	88,5	10	40	295			55-10-20	106TA8335
	3	88,6	9	29,5	290,5			55-10-25	124TA6188
	3	88,7	10	39,5	309,2			40-55-10	136TA3508
	3	88,8	10	40	315			50-10-25	135TA5486
	3	89	9	29	288			55-10-25	124TA6181
	3	89	9	34	345			40-50-05	106TA8395
	3	89	10	39	310			50-10-20	105TA5231
	3	89	10	40	339,3			50-05-20	135TA5490
	3	89	13	45,7	307			55-10-25	105TA5228
	3	92	10	39	308			50-10-25	116TA7199
	3	92	10	39	310			50-10-20	135TA5189
	3	92	11	39	305			40-55-10	116TA7166




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **LINDE-LANSING**



voltage (volt)	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
U	AT-BG	D1	AT-TA	D2	L	OLIED	TY-ST	LG-BG	
12	3	110	9	34	295			35-50-05	135TA5130
	3	110	9	34	295			50-05-20	135TA5141
	3	110	9	34	340			35-50-05	135TA5137
	3	110	9	34,5	338			35-50-05	135TA5375
24	0	55	9	34	420				106TA8393
	2	89	10	40	295		V	50-20	124TA6201
	3	88,5	10	40	316	V	V	55-10-25	135TA5569
	3	88,5	11	40	385			50-10-25	136TA3496
	3	88,7	11	40,7	404			50-05-25	136TA3506
	3	89	9	34	338			35-50-05	106TA8278
	3	89	9	34	340			35-50-10	124TA6134
	3	89	9	34	345			35-50-10	106TA8331



REF [135TA5130](#)



REF [135TA5141](#)



REF [135TA5137](#)



REF [135TA5375](#)



REF [106TA8393](#)



REF [124TA6201](#)



REF [135TA5569](#)



REF [136TA3496](#)



REF [136TA3506](#)



REF [106TA8278](#)



REF [124TA6134](#)




REF [106TA8331](#)

STARTERS

For all our latest catalogue updates and company info: www.tvh.com

used for: **LINDE-LANSING**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
24	3	89	11	40	385			40-55-20	106TA8307
	3	89	11	41	385		V	40-55-05	136TA3495
	3	92	11	55	358			45-05-25	135TA5575
	3	105	11	40,5	287		V	30-55-10	135TA5504
	3	110	9	34,2	372			35-50-05	135TA5407



REF [106TA8307](#)



REF [136TA3495](#)



REF [135TA5575](#)



REF [135TA5504](#)



REF [135TA5407](#)




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **LUGLI**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	95	9	32	235		V	40-10	135TA5155
	3	88,5	10	39	306			40-55-10	107TA9417
	3	88,5	10	39,5	277			40-50-10	135TA5573
	3	89	10	39	310			50-10-20	105TA5241




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **MANITOU**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	73,7	12	37	240			40-10	108TA4262
	2	74	9	29	215			45-10	106TA8384
	2	74	9	29	250			55-25	135TA5252
	2	74	13	38	248		V	45-10	103TA3436
	2	82,5	9	29	230			55-25	135TA5246
	2	82,5	9	35	290			50-20	135TA5360
	2	82,5	10	38	315			35-05	106TA5127
	2	83	10	39	320			40-10	107TA9614
	2	90	11	40	290	V	V	45-10	135TA5333
	3	66	9	25	197			40-55-10	135TA5515
	3	82	11	35	292			30-35-05	116TA7212
	3	88	10	39	307	V		35-50-10	103TA3570




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **MANITOU**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	88,5	9	34	295			35-50-05	135TA5193
	3	88,5	10	39	277			55-10-25	135TA5566
	3	88,5	10	39	306			40-55-10	107TA9416
	3	88,5	10	39,5	277			40-50-10	135TA5571
	3	88,7	9	34	324			40-50-10	106TA8389
	3	88,7	10	39,5	309,2			40-55-10	111TA1906
	3	89	10	28	232			55-10-25	135TA5602
	3	89	10	39	310			50-10-20	135TA5126
	3	89	10	39	330			55-05-20	106TA8386
	3	89	10	40	339,3			50-05-20	135TA5489
	3	89	11	40	315			40-05-20	105TA5244
	3	89	13	45,7	307			55-10-25	124TA6169




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **MANITOU**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	92	10	39	308			50-10-25	107TA9566
	3	92	10	39,5	306			55-10-25	108TA8634
	3	110	9	34	300			50-05-20	103TA3391
24	2	90	11	40	295	V	V	45-10	135TA5244
	2	105	11	40	295		V	50-20	135TA5240
	3	82,3	11	35	340			35-40-05	135TA5598
	3	88,8	10	39	340			35-55-05	135TA5592
	3	89	9	34	338			35-50-05	135TA5377
	3	92	12	45	365			40-60-20	135TA5288



REF [107TA9566](#)



REF [108TA8634](#)



REF [103TA3391](#)



REF [135TA5244](#)



REF [135TA5240](#)



REF [135TA5598](#)



REF [135TA5592](#)



REF [135TA5377](#)



REF [135TA5288](#)

STARTERS

Technical drawing of the AT-TA valve assembly. The drawing shows a side view of the valve with dimensions D1, D2, and L indicated. D1 is the total height, D2 is the height of the valve body, and L is the length of the valve body.




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **mitsubishi-caterpillar**



voltage (volt)	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch	reductor	position fixation points LG-BG	reference new
U	AT-BG	D1	AT-TA	D2	L	OLIED	TY-ST	LG-BG	
6	2	82	9	36	319			30-60	103TA3525
	3	88,5	9	36	322			30-45-60	106TA8297
	3	88,5	10	40	327			30-45-60	106TA8289
	3	88,5	13	46	362			30-45-60	106TA8293
12	2	60	14	42,7	230		V	45-20	135TA5599
	2	65,8	9	29,2	189			40-10	135TA5443
	2	67	8	28	245			35-05	135TA5645
	2	68	8	28	220			50-20	105TA5059
	2	68	11	29	245				136TA3534
	2	68	11	30	232				135TA5524
	2	70	8	28	230			35-05	105TA5285
	2	70	8	29	215			30-05	124TA6110




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **mitsubishi-caterpillar**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	70	9	28	230			35-05	136TA3559
	2	70	9	29	220			55-25	105TA5281
	2	70	9	29	230			30-05	105TA5290
	2	73,7	12	37	240			40-10	136TA3519
	2	74	8	26	226			40-05	105TA5277
	2	74	8	28	188			40-10	135TA5198
	2	74	8	28	194			40-10	136TA3514
	2	74	9	28,8	187,5		V	50-15	136TA8304
	2	74	9	29	190	V	V	50-20	135TA5357
	2	74	9	29	225			50-20	105TA5286
	2	74	9	29	235		V	45-10	103TA3430
	2	74	9	29,5	230			35-05	105TA5264



REF [136TA3559](#)



REF [105TA5281](#)



REF [105TA5290](#)



REF [136TA3519](#)



REF [105TA5277](#)



REF [135TA5198](#)



REF [136TA3514](#)



REF [136TA8304](#)



REF [135TA5357](#)



REF [105TA5286](#)



REF [103TA3430](#)




REF [105TA5264](#)

STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **mitsubishi-caterpillar**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	74	9	30	188			40-10	135TA5366
	2	74	11	34	228		V	45-15	105TA5309
	2	74	13	38	248		V	45-10	105TA5304
	2	75	13	39,8	202			50-20	136TA3550
	2	76,5	11	33,5	176	V	V	40-10	135TA5627
	2	76,8	8	28	189			40-10	136TA3538
	2	76,8	9	29,5	230			40-10	107TA9412
	2	76,8	15	44,8	226		V	40-10	106TA8251
	2	77	8	26	188			40-10	105TA5050
	2	77	8	28	183			40-10	106TA8354
	2	77	8	28	190			40-10	105TA5030
	2	77	8	28	207,5			40-10	135TA5616




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **mitsubishi-caterpillar**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	77	8	28,5	208			40-10	107TA9610
	2	77	9	29	192			40-10	105TA5850
	2	77	9	29	254	V		35-05	135TA5556
	2	77	10	31	210			40-10	135TA5341
	2	77	10	32,5	240		V	40-05	135TA5596
	2	77	10	33	240		V	40-10	105TA5051
	2	77	11	34	210		V	40-10	119TA7503
	2	77	11	34	220		V	40-10	105TA5032
	2	77	11	34	220		V	40-10	136TA3459
	2	77	11	34	220	V	V	40-10	116TA7182
	2	77	13	40	239		V	55-25	135TA5477
	2	77	13	41	240		V	55-25	105TA5283



REF [107TA9610](#)



REF [105TA5850](#)



REF [135TA5556](#)



REF [135TA5341](#)



REF [135TA5596](#)



REF [105TA5051](#)



REF [119TA7503](#)



REF [105TA5032](#)



REF [136TA3459](#)



REF [116TA7182](#)



REF [135TA5477](#)



REF [105TA5283](#)




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **mitsubishi-caterpillar**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	77	14	42,7	222	V		40-10	135TA5595
	2	77	15	45	220		V	40-10	105TA5852
	2	77	15	45	228		V	55-25	124TA6145
	2	82	8	27	185			35-05	105TA5289
	2	82	8	28	190			40-10	105TA5308
	2	82	8	29	210			55-25	116TA7143
	2	82	8	29	235			40-10	135TA5232
	2	82	9	25	300	V		45-15	105TA5024
	2	82	9	29	230			40-10	124TA6099
	2	82	9	29	250			50-20	105TA5869
	2	82	9	36	318			35-05	105TA5847
	2	82	10	38,8	240		V	50-20	136TA3539




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **mitsubishi-caterpillar**



voltage (volt)	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch	reductor	position fixation points LG-BG	reference new
U						OLIED	TY-ST		
12	2	82	10	39	305	V		35-05	135TA5093
	2	82	10	40	305	V		35-05	105TA5025
	2	82	11	34	240		V	40-10	105TA5266
	2	82,4	9	35	259			55-25	135TA5442
	2	82,4	11	34,5	238,5		V	40-10	103TA3246
	2	82,5	9	25	292				136TA3521
	2	82,5	9	29	200		V	55-25	135TA5275
	2	82,5	9	29	221,5			55-25	135TA5203
	2	82,5	9	29	243			35-05	106TA5112
	2	82,5	9	35	210		V	50-20	135TA5227
	2	82,5	9	35	225		V	55-25	124TA6114
	2	82,5	10	32,2	303			40-10	135TA5440




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **mitsubishi-caterpillar**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	82,5	10	38	258	V	V	55-25	124TA6190
	2	82,5	10	38	276		V	55-25	124TA6147
	2	82,5	10	38,5	252	V	V	50-25	135TA5525
	2	82,5	10	38,5	288			50-20	135TA5563
	2	82,5	10	40	220		V	40-15	135TA5320
	2	82,5	11	34	225		V	35-05	136TA3477
	2	82,5	11	34	230		V	55-25	124TA6124
	2	82,5	11	41	248		V	40-10	105TA5259
	2	82,5	11	42	215		V	45-15	124TA6149
	2	82,5	13	39	242	V	V	50-20	103TA3575
	2	88,8	10	40	233		V	40-10	135TA5545
	2	89	10	40	220		V	40-10	124TA6061



REF [124TA6190](#)



REF [124TA6147](#)



REF [135TA5525](#)



REF [135TA5563](#)



REF [135TA5320](#)



REF [136TA3477](#)



REF [124TA6124](#)



REF [105TA5259](#)



REF [124TA6149](#)



REF [103TA3575](#)



REF [135TA5545](#)



REF [124TA6061](#)




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **mitsubishi-caterpillar**



voltage (volt)	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch	reductor	position fixation points LG-BG	reference new
U	AT-BG	D1	AT-TA	D2	L	OLIED	TY-ST	LG-BG	
12	2	90	11	40	290	V	V	45-10	105TA5282
	2	95	9	31,8	243		V	40-10	135TA5638
	2	95	9	32	233		V	40-10	107TA9405
	2	95	9	32	235		V	40-10	135TA5153
	2	95	9	32	235		V	35-05	135TA5169
	2	95	9	32	315		V	40-10	135TA5180
	2	95	9	35	224		V	50-20	106TA8333
	3	65	12	0	229	V		35-50-05	135TA5533
	3	65	12	32	222			35-50-05	107TA9560
	3	65	13	32	190			35-50-05	105TA5306
	3	66	9	25	190			40-55-05	103TA3393
	3	73,8	10	31,5	208			50-05-20	105TA5311



REF [105TA5282](#)



REF [135TA5638](#)



REF [107TA9405](#)



REF [135TA5153](#)



REF [135TA5169](#)



REF [135TA5180](#)



REF [106TA8333](#)



REF [135TA5533](#)



REF [107TA9560](#)



REF [105TA5306](#)



REF [103TA3393](#)



REF [105TA5311](#)




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **mitsubishi-caterpillar**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	74	9	29	210		V	40-50-10	135TA5098
	3	74	9	29	210		V	40-50-10	135TA5368
	3	74	9	29	230		V	40-50-10	116TA7056
	3	74	9	29	230		V	40-50-10	105TA5038
	3	74	10	31	208			50-05-20	103TA3577
	3	88	10	39,5	340	V		35-50-05	135TA5459
	3	88,5	9	29	225		V	40-55-10	105TA5016
	3	88,5	9	29	305			30-45-60	105TA5048
	3	88,5	9	29	305	V		40-55-10	105TA5021
	3	88,5	10	38	310	V		35-50-05	105TA5017
	3	88,5	10	39	306	V		35-50-05	105TA5019
	3	88,5	10	40	290		V	40-55-10	105TA5057



REF [135TA5098](#)



REF [135TA5368](#)



REF [116TA7056](#)



REF [105TA5038](#)



REF [103TA3577](#)



REF [135TA5459](#)



REF [105TA5016](#)



REF [105TA5048](#)



REF [105TA5021](#)



REF [105TA5017](#)



REF [105TA5019](#)



REF [105TA5057](#)




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **mitsubishi-caterpillar**



voltage (volt)	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch	reductor	position fixation points LG-BG	reference new
U	AT-BG	D1	AT-TA	D2	L	OLIED	TY-ST	LG-BG	
12	3	88,5	10	40	305	V		35-50-05	105TA5027
	3	88,5	10	40	340		V	55-10-20	135TA5161
	3	88,5	10	40	345	V		35-50-05	105TA5848
	3	88,5	10	40	405	V		55-05-20	105TA5036
	3	88,7	10	39	405			50-05-25	105TA5018
	3	88,8	10	40	285	V	V	40-55-10	105TA5058
	3	88,8	12	37	287			50-10-20	135TA5539
	3	89	10	37,6	295		V	55-10-25	136TA3551
	3	89	10	39	225	V	V	40-55-10	124TA6090
	3	89	10	39	405			35-50-05	107TA9415
	3	89	10	40	290		V	55-10-25	135TA5096
	3	89	10	40	324	V		40-50-10	135TA5482




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **mitsubishi-caterpillar**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	89	10	40,3	294		V	50-10-25	136TA3558
	3	89,5	10	32	305	V		55-10-25	135TA5143
	3	92	11	55	460			30-55-05	105TA5035
	3	92	12	46	460			35-50-10	105TA5026
	3	92	12	46	475			55-10-30	124TA6183
	3	100	11	34	305			40-55-10	135TA5195
	3	100	12	48	305			55-10-25	136TA3482
	3	100	13	51	240		V	50-05-20	116TA7172
	3	100	13	51	264		V	55-10-25	105TA5275
	3	100	13	51	265		V	55-10-25	136TA3483
	3	100	13	51	275		V	55-10-25	136TA3489
	3	105	11	40	295		V	35-50-10	106TA8329



REF [136TA3558](#)



REF [135TA5143](#)



REF [105TA5035](#)



REF [105TA5026](#)



REF [124TA6183](#)



REF [135TA5195](#)



REF [136TA3482](#)




REF [116TA7172](#)



REF [105TA5275](#)



REF [136TA3483](#)



REF [136TA3489](#)



REF [106TA8329](#)




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **mitsubishi-caterpillar**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
24	2	82	10	32	275			40-10	105TA5257
	2	82	11	34	250		V	40-10	124TA6100
	2	82	11	34	305			40-10	135TA5199
	2	82	11	41	250	V	V	40-10	106TA8352
	2	82	11	41,5	250		V	40-10	103TA3241
	2	82	13	39	240		V	40-10	105TA5867
	2	82,5	9	35	242		V	35-05	135TA5215
	2	82,5	10	38	288		V	50-20	135TA5295
	2	82,5	10	38,5	253	V	V	55-25	136TA3556
	2	82,5	10	39	288			35-05	135TA5614
	2	82,5	10	39	290		V	40-10	105TA5031
	2	89,6	9	31,5	284		V	50-20	106TA8264




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **mitsubishi-caterpillar**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
24	2	95	11	37,5	258	V		40-05	135TA5560
	2	95	11	40,8	287			40-10	136TA3529
	2	100	12	45	266		V	45-15	106TA8318
	2	110	11	40	290		V	55-20	105TA5043
	3	60	9	35	240		V	40-60-10	105TA5053
	3	88,5	12	46	402			50-10-20	106TA8247
	3	89	12	43	321	V		35-50-05	135TA5642
	3	89	12	44	322			35-50-05	135TA5604
	3	91,5	11	56	519			35-50-05	135TA5455
	3	91,5	12	46	480			35-55-15	107TA9401
	3	91,7	12	46	450			45-05-25	107TA9605
	3	91,7	12	46	475			30-50-05	105TA5045




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **mitsubishi-caterpillar**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
24	3	92	11	0	520			45-05-25	136TA3548
	3	92	11	56	480			35-55-15	105TA5033
	3	100	12	45	265		V	45-60-15	136TA3467
	3	100	12	45	290		V	40-55-10	136TA3466
	3	101	12	44,5	550			35-55-10	107TA9589
	3	105	11	40	300		V	35-50-10	116TA7221
	3	105	11	40	346			35-50-05	135TA5290




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **MOFFETT**




voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	65,8	9	29,2	189			40-10	135TA5445
	2	66	9	29	195		V	40-10	135TA5183
	2	66	9	29,3	208			40-10	135TA5406
	2	77	13	41	240		V	55-25	135TA5309
	2	77	15	45	228		V	55-25	135TA5310
	2	82,5	9	34	210		V	40-10	135TA5313





used for: **MORA**



STARTERS

voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	89	10	39	310			50-10-20	105TA5312



REF [105TA5312](#)




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **NIFTYLIFT**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	74,8	11	0	204			55-25	135TA5499



REF [135TA5499](#)


STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **NISSAN**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	70	8	28	220			35-05	103TA3280
	2	70	8	29	215			30-05	105TA5318
	2	70	9	29	220			55-25	105TA5313
	2	70	9	29	230			30-05	103TA3261
	2	75	13	39,8	202			50-20	136TA3549
	2	76,5	11	33,5	176	V	V	40-10	135TA5628
	2	76,8	8	28	189			40-10	136TA3537
	2	77	8	28	190			40-10	124TA6095
	2	77	10	31	210			40-10	124TA6157
	2	77	11	34	220		V	40-10	124TA6102
	2	80	9	29	210			40-10	106TA8361
	2	82	8	27	185			35-05	105TA5320



REF [103TA3280](#)



REF [105TA5318](#)



REF [105TA5313](#)



REF [103TA3261](#)



REF [136TA3549](#)



REF [135TA5628](#)



REF [136TA3537](#)



REF [124TA6095](#)



REF [124TA6157](#)



REF [124TA6102](#)



REF [106TA8361](#)




REF [105TA5320](#)

STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **NISSAN**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	82	8	28	190			40-10	135TA5221
	2	82	8	29	210			55-25	116TA7138
	2	82	8	29	235			40-10	135TA5229
	2	82	9	29	210	V	V	40-10	103TA3268
	2	82	9	29	232			40-10	105TA5321
	2	82	9	29	260			50-20	103TA3275
	2	82	9	29	313			55-25	105TA5315
	2	82,5	9	29	195		V	35-05	135TA5206
	2	82,5	9	29	197		V	55-25	105TA5325
	2	82,5	9	29	198		V	55-25	103TA3584
	2	82,5	9	29	200		V	55-25	135TA5273
	2	82,5	9	29	221,5			55-25	135TA5202



REF [135TA5221](#)



REF [116TA7138](#)



REF [135TA5229](#)



REF [103TA3268](#)



REF [105TA5321](#)



REF [103TA3275](#)



REF [105TA5315](#)



REF [135TA5206](#)



REF [105TA5325](#)



REF [103TA3584](#)



REF [135TA5273](#)



REF [135TA5202](#)




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **NISSAN**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	82,5	9	29	230			55-25	105TA5319
	2	82,5	9	29	243			35-05	106TA5111
	2	82,5	9	35	210		V	50-20	135TA5228
	2	82,5	9	35	210		V	50-20	103TA3270
	2	82,5	9	35	218,5		V	40-05	135TA5495
	2	82,5	9	35	225		V	55-25	105TA5333
	2	82,5	9	35	225		V	55-25	105TA5490
	2	82,5	9	35	245		V	35-05	106TA8319
	2	82,5	9	35	285			35-05	105TA5322
	2	82,5	10	38	258	V	V	55-25	135TA5394
	2	82,5	10	38	276		V	55-25	136TA3492
	2	82,5	11	34	225		V	35-05	103TA3272




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **NISSAN**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	82,5	11	34	230		V	55-25	103TA3283
	2	82,5	11	42	215		V	45-15	105TA5316
	2	83,3	9	29,2	210		V	35-05	135TA5452
	2	94,9	9	35,6	223,5		V	50-20	135TA5635
	2	95	9	32	230		V	40-10	135TA5416
	2	95	9	32	230		V	40-10	107TA9578
	2	95	9	32	305			40-10	106TA8360
	2	95	9	35	224		V	50-20	136TA3518
	2	95	9	35	228		V	35-05	124TA6136
	2	95	9	35,6	223		V	45-15	136TA3515
	2	95	11	38	292		V	40-10	116TA7167
	3	88,5	9	29	305	V		30-45-60	124TA6069



REF [103TA3283](#)



REF [105TA5316](#)



REF [135TA5452](#)



REF [135TA5635](#)



REF [135TA5416](#)



REF [107TA9578](#)



REF [106TA8360](#)



REF [136TA3518](#)



REF [124TA6136](#)



REF [136TA3515](#)



REF [116TA7167](#)



REF [124TA6069](#)




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **NISSAN**



voltage (volt)	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch	reductor	position fixation points LG-BG	reference new
U	AT-BG	D1	AT-TA	D2	L	OLIED	TY-ST	LG-BG	
12	3	88,5	10	39	310			35-50-05	124TA6066
	3	88,5	10	39	340	V	V	35-50-10	124TA6154
	3	88,5	12	46	345			55-10-25	135TA5146
	3	100	13	51	240		V	50-05-20	105TA5327
	3	105	11	40	238		V	45-05-20	135TA5555
	3	105	11	40	305			40-55-05	105TA5314
24	2	82,5	9	35	242		V	35-05	105TA5323
	2	82,5	10	27	275			35-05	111TA1908
	2	82,5	10	38	288		V	50-20	135TA5296
	2	82,5	10	39	288			35-05	135TA5612
	2	95	9	34,8	236	V	V	50-20	135TA5500
	2	105	11	40	295		V	40-10	105TA5324



REF [124TA6066](#)



REF [124TA6154](#)



REF [135TA5146](#)



REF [105TA5327](#)



REF [135TA5555](#)



REF [105TA5314](#)



REF [105TA5323](#)



REF [111TA1908](#)



REF [135TA5296](#)



REF [135TA5612](#)



REF [135TA5500](#)



REF [105TA5324](#)




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **NISSAN**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
24	3	105	11	40	300			40-55-10	103TA3265
	3	105	11	40	300		V	35-50-10	136TA3512
	3	105	11	40	304		V	40-55-10	103TA3281
	3	105	11	40	306			40-50-10	107TA9602
	3	105	11	40	339		V	45-05-15	136TA3480



REF [103TA3265](#)



REF [136TA3512](#)



REF [103TA3281](#)



REF [107TA9602](#)




REF [136TA3480](#)

STARTERS

For all our latest catalogue updates and company info: www.tvh.com



used for: **O&K**



STARTERS

voltage (volt)	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
U									
12	2	74	9	29	215			45-10	135TA5399
	2	74	13	38	248		V	45-10	135TA5305
	2	82,5	9	25	285			55-25	135TA5266
	2	89	10	40	290		V	40-10	135TA5109
24	3	89	9	34	338			35-50-05	135TA5378



REF [135TA5399](#)



REF [135TA5305](#)



REF [135TA5266](#)



REF [135TA5109](#)




REF [135TA5378](#)

STARTERS

For all our latest catalogue updates and company info: www.tvh.com

used for: **OM PIMESPO**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	66	9	25,2	212			40-10	107TA9403
	2	82	9	29	260			50-20	136TA3479
	2	82,5	9	29	195		V	35-05	136TA3474
	2	82,5	9	29	230			55-25	135TA5248
	2	82,5	9	34	255			35-05	135TA5464
	2	82,5	9	35	210		V	50-20	136TA3478
	2	89	10	40	187		V	50-20	135TA5133
	2	95	9	35	228		V	35-05	135TA5585
	3	82	9	25	260			55-05-25	106TA8299
	3	82	9	25	265			35-50-05	106TA8267
	3	82	11	29	225			35-50-05	105TA5113
	3	82,5	9	25	223			35-50-05	103TA3544



REF [107TA9403](#)



REF [136TA3479](#)



REF [136TA3474](#)



REF [135TA5248](#)



REF [135TA5464](#)



REF [136TA3478](#)



REF [135TA5133](#)



REF [135TA5585](#)



REF [106TA8299](#)



REF [106TA8267](#)



REF [105TA5113](#)



REF [103TA3544](#)




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **OM PIMESPO**




voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	82,5	10	27	260			35-50-05	105TA5114
	3	82,5	11	29	253			30-05-15	105TA5856
	3	88,5	9	34	340			55-10-25	105TA5122
	3	88,8	10	40	315			50-10-25	135TA5485
	3	94,8	9	34	370			50-05-20	103TA3174
	3	94,8	9	34,3	371			40-55-25	105TA5111
	3	110	9	34	293			55-05-20	135TA5615
	3	110	9	34	295			50-05-20	135TA5140
	3	110	9	34	295			35-50-05	105TA5116
	3	110	9	34	300			35-45-05	103TA3542
	3	110	9	34	340			35-50-05	135TA5136
	3	110	9	34	340			50-05-20	105TA5119



STARTERS

For all our latest catalogue updates and company info: www.tvh.com

used for: **OM PIMESPO**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	110	9	34,5	338			35-50-05	105TA5118
24	2	89	10	40	295		V	50-20	136TA3525
	2	100	12	45	266		V	45-15	136TA3494
	3	100	13	46	363			35-50-10	136TA3501
	3	110	9	34	290			35-50-05	105TA5120
	3	110	9	34	340			35-50-05	105TA5117
	3	110	9	34,2	372			35-50-05	106TA5124
	3	115	11	40	405			50-05-25	106TA8258




STARTERS

For all our latest catalogue updates and company info: www.tvh.com



used for: **OMG**



STARTERS

voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	82,5	9	29	195		V	35-05	135TA5212
	2	95	9	32	235		V	35-05	135TA5174
	2	95	9	32	235		V	40-10	135TA5158

